



SPECIFICATIONS

Front I/O Ports	1 x USB 3.0 + 2 x USB 2.0 + HD Audio / Mic
Power Supply	Standard ATX
WEIGHT (CARD)	169g
Quantidade de ventiladores	2
Dimensões do ventilador	120 x 120 x 25mm / 4.7 x 4.7 x 0.98 inches
Velocidade do ventilador	500 ~ 2000 RPM
Consumo do ventilador	1.8 W
Corrente nominal do ventilador	0.15 A
Rolamento do ventilador	Two Ball Bearing
Nível de ruído do ventilador	14.3 ~ 34.3 dBA
Fluxo de ar do ventilador	21.63 ~ 78.73 CFM
Iluminação do ventilador	ARGB
Comprimento do cabo de ventilador (cabo 5V ARGB / PWM)	550 / 350mm; 21.65 / 13.78 inches
Material do Radiador	Aluminum
Dimensões do Radiador	274 x 120 x 27mm / 10.79 x 4.7 x 1.06 inches
Dimensões do bloco	80.57x 66.82 x 48.58mm / 3.17 x 2.63 x 1.91 inches
PWM Mode	Yes
Fan Included	Addressable RGB Fan x 1
Fan Speed	600 ± 200 ~ 1000 ± 10% RPM
Fan Connector	3-Pin (ARGB) / 4-Pin (PWM)
Air Pressure	1.1 mmH2O
Velocidade da bomba	4200 ±10%RPM
Consumo da bomba	4.08W
Dimensions	120mm x 120mm x 25.6mm
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
Soquete Intel	LGA 1150/1151/1155/1156/1200/1700 LGA 1366/2011/2011-3/2066
Weight	262g
Soquete AMD	AM5/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2
Acessórios	1 to 2 Fan PWM cable x 1 PSU Molex 4-Pin to 4-Pin(2 Pin Wired) Fan cable x 1