



FEATURES

SPECIFICATIONS

Number of Fans	3
Fan Speed	500 ~ 2000 RPM
Fan Power Consumption	1.8 W
Fan Rated Current	0.15 A
Fan Rated Voltage	12V DC
Fan Bearing	Two Ball Bearing
Fan Air Pressure	0.23 ~ 2.39 mmH ₂ O
Fan Noise Level	14.3 ~ 34.3 dBA
Fan Air Flow	21.63 ~ 78.73 CFM
Fan Dimensions (WxDxH)	120 x 120 x 25mm / 4.7 x 4.7 x 0.98 inches
Fan Lighting	ARGB
Fan ARGB Cable Connector	Pin + Socket
PWM Mode	Yes
Fan Cable Length (5V ARGB / PWM cable)	550 / 350mm; 21.65 / 13.78 inches
Radiator Material	Aluminum
Radiator Dimensions	394 x 120 x 27mm / 15.5 x 4.7 x 1.06 inches
Radiator Water Cooling Pipe Length	400mm / 15.75 inches
Block Dimensions	80.57x 66.82 x 48.58mm / 3.17 x 2.63 x 1.91 inches
Block Lighting	ARGB
Fan Included	Addressable RGB Fan x 1
Block ARGB 5V Cable Length	400mm / 15.75 inches
Block ARGB Cable Connector	Pin + Socket
Fan Speed	600 ± 200 ~ 1000 ± 10% RPM
Fan Noise Level	25 dBA
Fan Connector	3-Pin (ARGB) / 4-Pin (PWM)
Pump Load Current	0.34 A
Light	Addressable RGB
Air Flow	89 CFM
Pump Rated Voltage	12V DC
Pump Speed	4200 ±10%RPM
Air Pressure	1.1 mmH ₂ O
Pump Power Consumption	4.08W
Rated Voltage	12 VDC
Rated Current	0.30A ~ 0.35A
Bearing Type	Sleeve Bearing
Intel Socket	LGA 1150/1151/1155/1156/1200/1700 LGA 1366/2011/2011-3/2066
Weight	262g
AMD Socket	AM5/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2 SocketTR4/sTRX4/SP3
AMD SocketTR4 / sTRX4 / SP3 Socket	Y
Accessories	1 to 3 Fan PWM cable x 1 PSU Molex 4-Pin to 4-Pin(2 Pin Wired) Fan cable x 1 Noise reducer cable x 1
Dimensions	195 x 195 x25 mm / 7.68 x 7.68 x 1 inch