



SPECIFICATIONS

Front I/O Ports	2 x USB 3.0 + HD Audio / Mic
VGA Card Support	Max 400mm / 15.75 inch
CPU Cooler Support	Max 170mm / 6.69 inch
Power Supply	Standard ATX
WEIGHT (CARD)	169g
Number of Fans	1
Fan Dimensions	120 x 120 x 25mm / 4.7 x 4.7 x 0.98 inches
Fan Speed	500 ~ 2000 RPM
Radiator Compatibility	120 / 140 / 240 mm
Fan Power Consumption	3 W
Fan Rated Current	0.25 A
Fan Life Expectancy	40,000 hours
Fan Bearing	Long Life Bearing
Fan Noise Level	14.3 ~ 34.3 dBA
Fan Air Flow	21.63 ~ 78.73 CFM
Fan Lighting	Auto-RGB
Fan Cable Length (5V ARGB / PWM cable)	NA / 350mm±10mm; NA / 13.78 inches
Radiator Material	Aluminum
Radiator Dimensions	154 x 120 x 27mm / 6.06 x 4.7 x 1.06 inches
Block Dimensions	Φ70x46 mm
Pump Life Expectancy	100,000 hours
Pump Noise Level	18 dBA
Pump Speed	4200 RPM +/-10%
Dimensions	120mm x 120mm x 25.6mm
Pump Power Consumption	4.08W
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Noise Level (Fans)	17.2 - 33.6 dBA



LIQUID COOLING

MAG CORELIQUID B120

DROWN ALL OPPOSITION

Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
Intel Socket	LGA 1851/1150/1151/1155/1156/1200/1700 LGA 2011/2011-3/2066
AMD Socket	AM5/AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2
Accessories	NA
Radiator Size	120 mm
Cold Plate Material	Copper