



## FEATURES

## SPECIFICATIONS

<b>Number of Fans</b>	3
<b>Fan Dimensions</b>	120 x 120 x 25 mm / 4.7 x 4.7 x 0.98 inches
<b>Fan Speed</b>	0 ~ 2000 RPM
<b>Fan Power Consumption</b>	4.8 W (MAX)
<b>Fan Rated Current</b>	0.4 A (MAX)
<b>Fan Life Expectancy</b>	50,000 Hours
<b>Fan Bearing</b>	Hydro-Dynamic Bearing
<b>Fan Air Pressure</b>	2.21 mmH2O
<b>Fan Noise Level</b>	22.7 dBA
<b>Fan Air Flow</b>	56.2 CFM
<b>Fan Lighting</b>	NA
<b>Fan ARGB Cable Connector</b>	NA
<b>PWM Mode</b>	Yes
<b>Fan Cable Length (5V ARGB / PWM cable)</b>	350 mm / 13.78 inches
<b>Radiator Material</b>	Aluminum
<b>Radiator Dimensions</b>	394 x 120 x 27 mm / 15.5 x 4.7 x 1.06 inches
<b>Radiator Water Cooling Pipe Length</b>	400mm / 15.75 inches
<b>Block Dimensions</b>	95 x 95 x 83.53 mm
<b>Pump Life Expectancy</b>	50,000 Hours
<b>Pump Noise Level</b>	21.2 dBA
<b>Pump Load Current</b>	0.33 A
<b>Pump Speed</b>	2800 +/-300 RPM (PWM controlled)
<b>Pump Power Consumption</b>	4W
<b>Intel Socket</b>	"LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 / LGA 2066 / 2011-3 / 2011"
<b>AMD Socket</b>	"AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1 / Socket TR4 / sTRX4 / SP3"
<b>Accessories</b>	NA
	4 pin PWM
	USB 2.0 pin header
	500 nits
	16 bits
	320 x 240
	IPS
	2.4"
<b>Cold Plate Material</b>	Copper
	Black Rubber + Mesh
	0.33A
	NA
	4 pin PWM
	2.21 mm H2O
	400 mm
<b>Radiator Size</b>	360 mm
	SATA