



msi

LIQUID-COOLING

MAG CORELIQUID 280R V2



FEATURES

SPECIFICATIONS

Количество вентиляторов	2
Размеры вентиляторов	140 x 140 x 25мм / 5.51 x 5.51 x 0.98 дюймов
Fan Speed	500 ~ 1800 об/мин
Fan Power Consumption	2.28 W
Fan Rated Current	0.19 A
Fan Rated Voltage	12V DC
Fan Bearing	Двойной шарикоподшипник
Fan Air Pressure	2.29 mm-H2O
Fan Noise Level	14.8~33.28 дБА
Fan Air Flow	84.36 CFM
Fan Lighting	ARGB - адресуемая
Fan ARGB Cable Connector	Pin + Socket
PWM Mode	Yes
Fan Cable Length (5V ARGB / PWM cable)	550 / 350мм; 21.65 / 13.78 дюймов
Radiator Material	Алюминий
Radiator Dimensions	312 x 140 x 27мм / 12.28 x 5.51 x 1.06 дюймов
Radiator Water Cooling Pipe Length	400мм / 15.75 дюймов
Block Dimensions	80.57x 66.82 x 48.58мм / 3.17 x 2.63 x 1.91 дюймов
Block Lighting	ARGB - адресуемая
Block ARGB 5V Cable Length	400мм / 15.75 дюймов
Block ARGB Cable Connector	Pin + Socket
Pump Load Current	0.34 A
Pump Rated Voltage	12V DC
Pump Speed	4200 об/мин
Pump Power Consumption	4.08W
Сокеты Intel	LGA 1150/1151/1155/1156/1200/1700 LGA 1366/2011/2011-3/2066
Сокеты AMD	AM4/FM2+/FM2/FM1/AM3+/AM3/AM2+/AM2
Аксессуары	1 to 2 Fan PWM cable x 1 PSU Molex 4-Pin to 4-Pin(2 Pin Wired) Fan cable x 1

Generated 2022-03-18, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.