




FEATURES



SPECIFICATIONS

Compatible CPU	Suggest to work with Intel LGA2066 Core i9/ i7 (44-Lanes) and AMD Ryzen Threadripper processors for the best performance
Interface	PCI Express 3.0 x16 interface Compatible with PCI Express x16 slot
External connector	4x M.2 slot (Key M) - Support up to PCIe3.0 x 16 bandwidth - Supports 2242 / 2260 / 2280 / 22110 storage devices (PCIe SSD only) - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host Card 1 x 6-pin ATX PCIe power connector 1 x 4-pin FAN power connector 2 x 2-pin Front panel
LED	4 x M.2 easy access LEDs - these LEDs will flash when any M.2 SSD be accessed. 6 x M.2 temperature detection LEDs - these LEDs will change color according to the temperatures of M.2 SSDs.
RAID Support	Intel VROC Ready with Intel RSTe for X299 Series motherboards
Dimensions	175x135x38.8 mm
Accessory	1 x HDD LED Cable

CONNECTIONS



- | | |
|-----------------------------|-----------------------------------|
| 1. LED Switch | 2. FAN Switch |
| 3. ATX PCIe Power connector | 4. 4 x Turbo M.2 slots |
| 5. M.2 easy access LEDs | 6. M.2 temperature detection LEDs |
| 7. Front panel connectors | |