



SPECIFICATIONS

Model Name	MAG B660M MORTAR WIFI
CPU Support	Supports 12 th Gen Intel® Core™ Processors, Pentium® Gold and Celeron® Processors
CPU Socket	LGA 1700
Chipset	Intel® B660 Chipset
Graphics Interface	1x PCIe 4.0 x16 slot, 1x PCIe 3.0 x16 slot Supports AMD® CrossFire™ Technology
Display Interface	Support 4K@60Hz as specified in HDMI™ 2.1, DisplayPort 1.4 - Requires Processor Graphics
Memory Support	4 DIMMs, Dual Channel DDR5-6200+ (OC)
Expansion Slots	1x PCIe 3.0 x1 slot
Storage	2x M.2 Gen4 x4 64Gbps slots, Support Intel® Optane™ Technology, 6x SATA 6Gb/s ports
USB ports	1x USB 3.2 Gen 2x2 20Gbps (Type-C), 4x USB 3.2 Gen 2 10Gbps (3 Type-A + 1 Type-C), 2x USB 3.2 Gen 1 5Gbps (Type-A), 8x USB 2.0
LAN	1x Realtek® RTL8125BG 2.5Gbps LAN
Wireless / Bluetooth	Intel® Wi-Fi 6E module, Bluetooth 5.2
Audio	8-Channel (7.1) HD Audio

FEATURES



Lightning Gen4 Solution

The latest Gen4 PCI-E and M.2 solution with up to 64GB/s bandwidth for maximum transfer speed.



Extended Heatsink Design

MSI extended PWM heatsink and enhanced circuit design ensures even high-end processors to run in full speed.



Latest DDR5 Memory

A huge step of DDR performance enhancement with the latest DDR5 memory and MSI Memory Boost technology.



Wi-Fi 6E

The latest wireless solution supports 6GHz spectrum, MU-MIMO and BSS color technology, delivering speeds up to 2400Mbps.



M.2 Shield FROZR

M.2 thermal accessory keeps M.2 SSDs safe while preventing throttling, making them run faster.



Core Boost

With premium layout and fully digital power design to support more cores and provide better performance.



2.5G Network Solution


Featuring premium 2.5G LAN to deliver better network experience.



Lightning USB 20G

Built-in USB 3.2 Gen 2x2 port, offers 20Gbps transmission speed, 4X faster than USB 3.2 Gen 1.

CONNECTIONS



1. USB 2.0 Port
2. DisplayPort 1.4
3. USB 3.2 Gen 2 10Gbps Type-A
4. 2.5G LAN Port
5. Wi-Fi / Bluetooth Antenna
6. HD Audio Connectors
7. HDMI™ 2.1 Port
8. USB 3.2 Gen 2x2 20Gbps Type-C
9. Optical S/PDIF OUT