



SPECIFICATIONS

Contrast Ratio	1500000:1
Tecnologia Dynamic Refresh Rate	AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48 ~ 165Hz
Adobe RGB / DCI-P3 / sRGB	97.5% / 99% / 138.2%
Dimension (W x D x H)	717 x 242 x 457 mm 717 x 72 x 419 mm (without stand)
Carton Dimension (W X D X H)	WW carton: 972 x 185 x 513 mm Outer: 990 x 200 x 538 mm
Tamanho Painel	31.5"
Relação de Aspecto	16:9
Resolução Painel	3840x2160 (UHD)
Distância entre Pixeis (H x V)	0.1814(H) x 0.1814(V)
Taxa de atualização	165Hz
Tempo de resposta	0.03ms (GTG)
Ângulo de visão	178°(H) / 178°(V)
Curvo	Flat
Brilho	250
Ajuste (Pivot)	-10° ~ 10°
Design sem bordas	Yes
Peso	9.1kg / 11.8kg
Tipo de painel	QD-OLED
Área de visualização ativa (mm)	699.48(H) x 394.73(V)
Tratamento da superfície	Anti-Reflection
Cores da tela	1.07B, 10 bits
Portas de vídeo	1x Display Port 1.4a 2x HDMI™ 2.1 (4K@165Hz) 1x USB 2.0 Type-C (DP alt.) w/ 15W PD
Portas de áudio	1x Headphone-out
Kensington Lock	Yes
Montagem VESA	100 x 100 mm
Tipo de energia	Power Cable
Entrada de energia	100~240V, 50/60Hz
Frequência de sinal	30~390KHz (H) / 48 ~ 165Hz(V)
Ajustes (Inclinação)	-5° ~ 15°
Ajustes (Giro)	30° ~ 30°
Ajustes (Altura)	0 ~ 110mm

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Nota	Display Port: 3840 x 2160 (Up to 165Hz)
	HDMI™: 3840 x 2160 (Up to 165Hz)
	Type-C (DP alt.): 3840 x 2160 (Up to 165Hz) w/ 15W PD *sRGB and DCI-P3 follow CIE1976 standard
Suporte HDR	DisplayHDR True Black 400
Função PIP / PBP	N/A
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2 x HDMI™ 2.1(UHD@165Hz)
4. Display Port 1.4a
5. USB Type-C (PD 15W)
6. Earphone out
7. Kensington lock