



SPECIFICATIONS

Contrast Ratio	1500000:1 (Typ.)
DCR	N/A
Tecnologia Dynamic Refresh Rate	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48~165Hz
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Carton Dimension (W X D X H)	935 x 185 x 513 mm (36.81 x 7.28 x 20.20 inch)
Tamanho Painel	31.5"
Relação de Aspecto	16:9
Resolução Painel	3840 x 2160 (UHD)
Distância entre Pixeis (H x V)	0.1814 (H) x 0.1814 (V)
Taxa de atualização	165Hz
Tempo de resposta	0.03ms (GTG)
Ângulo de visão	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	719.1 x 241.9 x 593.9 mm (28.31 x 9.52 x 23.38 inch)
Curvo	Flat
Dimension without Stand (W x D x H)	719.1 x 69.3 x 418.3 mm (28.31 x 2.73 x 16.47 inch)
Brilho	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Ajuste (Pivot)	-10° ~ 10°
Modo Console	Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz 1440p: 60Hz and 120Hz 2160p: 60Hz and 120Hz
	HDMI™ CEC: Supported VRR: PS5 and Xbox Supported
Peso	7.7 kg (16.98 lbs) / 12.3 (27.1 lbs)
Tipo de painel	QD-OLED
Área de visualização ativa (mm)	699.48 (H) x 394.73 (V)
Tratamento da superfície	Anti-Reflection
Cores da tela	1.07B, 10 bits
Portas de vídeo	2x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Portas USB	N/A

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Portas de áudio	1x Headphone-out
Kensington Lock	Yes
Montagem VESA	100 x 100 mm
Tipo de energia	Internal Power Board
Entrada de energia	100~240V, 50/60Hz
Frequência de sinal	30~390KHz (H) / 48 ~ 165Hz (V)
Ajustes (Inclinação)	-5° ~ 15°
Ajustes (Giro)	-30° ~ 30°
Ajustes (Altura)	0 ~ 110 mm
Nota	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Suporte HDR	VESA DisplayHDR True Black 400
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw

CONNECTIONS



1. Headphone out
2. 2 x HDMI™ 2.1 (UHD@165Hz)
3. DisplayPort 1.4a (HBR3)
4. Type-C (DP alt.) w/ 15W PD
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock