



SPECIFICATIONS

Dimensions du carton (L x l x H)	820 x 169 x 513 mm
Taille de la dalle	26,5"
Temps de réponse	0,03 ms (gris à gris)
Encoche Kensington	Oui
Technologie de rafraîchissement dynamique	Adaptive-Sync
Plage de fréquences de rafraîchissement	48 ~ 240 Hz
Interface vidéo	1x DP(1.4) 2x HDMI™ (2.0) 1x USB Type-C (DisplayPort Alternate)
Adobe RGB / DCI-P3 / sRGB	98 % / 99 % / 138 % (norme CIE1976)
Dimensions avec pied de support (L x H x P)	610,31 x 241,9 x 532,03 mm
Dimensions sans pied de support (L x H x P)	610,31 x 69,15 x 356,4 mm
Mode Console	Résolution et taux de rafraîchissement supportés : 1080p : 60 Hz et 120 Hz 1440p : 60 Hz et 120 Hz 2160p : 60 Hz et 120 Hz
Interface audio	Support de la norme HDMI™ CEC VRR : consoles PS5 et Xbox supportées
Ports USB	1x Earphone out
Ports USB	N/A
Jacks audio	1 x sortie audio
Fixation VESA	100 x 100 mm
Entrée alimentation	100~240 V, 50/60 Hz
Remarques	HDMI™ : 3840 x 2160 (jusqu'à 240 Hz) DisplayPort : 3840 x 2160 (jusqu'à 240 Hz) Support : HDMI™ CEC, PIP/PBP ; non supporté : KVM
Support HDR	VESA DisplayHDR True Black 400

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



Taux de rafraîchissement élevé 240 Hz

Profitez d'un taux de rafraîchissement ultrarapide et gardez la tête du classement dans les jeux les plus rapides.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VEASA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Accessoires

1 x câble DisplayPort (1.4a)
1 x HDMI™ (2.1),
1 x câble d'alimentation (C13)
1 x guide de démarrage rapide
4 x vis de fixation VESA
1 x chiffonnette de nettoyage

Garantie

3 ans (incluant la protection contre les brûlures)

CONNECTIONS

1. Headphone out
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. DisplayPort 1.4a (HBR3)
4. USB Type-C (15W PD)
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock