MONITOR

MAG 341CQP QD-OLED X28





SPECIFICATIONS

VESA ClearMR Certified	VESA ClearMR 15000
Technologie Dynamické přepínání obnovovací frekvence	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48~280Hz
DCR	N/A
HDR Support	VESA DisplayHDR True Black 500
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 136% (CIE1976 Standard)
Carton Dimension (W X H X D)	1000 x 198 x 468 mm (39.37 x 7.80 x 18.43 inch)
Úhlopříčka	34.18"
Poměr stran	21:9
Rozlišení	3440 x 1440 (UWQHD)
Rozteč pixelů (H x V)	0.2315(H) x 0.2315(V)
Obnovovací frekvence	280Hz
Doba odezvy	0.03ms (GtG)
Pozorovací úhel	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	811.7 x 229.9 x 430.4mm (31.96 x 9.05 x 16.94 inch)
Zakřivení	Curve 1800R
Dimension without Stand (W x D x H)	811.7 x 131.3 x 361.2 mm (31.96 x 5.17 x 14.22 inch)
Jas	SDR: 300 HDR: 1300
Kontrast	1500000:1 (Typ.)
Bezrámečkový design	Yes
Váha	9.5 kg (20.94 lbs) / 14.4 kg (31.75 lbs)
Typ panelu	QD-OLED
Active Display Area (mm)	800.06(H) x 337.06(V)
Povrchová úprava	Anti-Reflection
Zobrazených barev	1.07B, 10 bits
Video porty	2x HDMI™ 2.1 (UWQHD@280Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Audio porty	1x Headphone-out
Zabezpečení Kensington	Yes
Montáž VESA	100 x 100 mm
Typ napájení	Internal Power Board
Příkon	100~240V, 50/60Hz
Frekvence signálu	461.2~464.8 KHz(H) / 48~280 Hz(V)

FEATURES

QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming

280Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.

0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.

OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.

Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA DisplayHDR True Black 500

It has passed the VESA DisplayHDR True Black 500 Certification, meaning it can provide a display with the most realistic colors.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

Nastavení náklonu	-5° ~ 20°
Nastavení otočení	-30° ~ 30°
Nastavení výšky	0 ~ 110 mm
Poznámky	HDMI™: 3440 x 1440 (Up to 280Hz) DisplayPort: 3440 x 1440 (Up to 280Hz) Type-C: 3440 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
PIP / PBP Funkce	Yes
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UWQHD@280Hz)
4. DisplayPort 1.4a
5. Type-C (DP alt.) w/ 15W PD
6. Headphone-out
7. Kensington Lock

Generated 2026-10-02, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.