

MAG 276CFDE E20





SPECIFICATIONS

Panel Size	27"
Panel Resolution	1920 x 1080 (FHD)
Refresh Rate	200Hz
Panel Type	Rapid VA
Brightness (nits)	SDR: 250 cd/m2
Viewing Angle	178° (H) / 178° (V)
Aspect Ratio	16:9
Curvature	Curve 1500R
Contrast Ratio	3000:1
Active Display Area (mm)	597.888 (H) x 336.312 (V)
Pixel Pitch (H x V)	0.3114 (H) x 0.3114 (V)
Surface Treatment	Anti-glare
Display Colors	1.07B, 10 bits (8 bits + FRC)
Adobe RGB / DCI-P3 / sRGB	81% / 76% / 98% (CIE1976 Standard)
Response time	0.5ms (GtG, Min.)
Video ports	1x HDMI™ 2.0b (FHD@200Hz) 1x DisplayPort 1.2a
USB ports	N/A
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
ACTIVATED RANGE	48~200Hz
DCR	100000000:1
HDR Support	HDR Ready
SPEAKER	N/A
Signal Frequency	53~221 KHz(H) / 48~200 Hz(V)
Adjustment (Tilt)	-5°~20°
Adjustment (Swivel)	N/A
Adjustment (Pivot)	N/A
Adjustment (Height)	N/A
Carton Dimension (W X D X H)	684 x 158 x 475 mm (26.9 x 6.22 x 18.7 inch)
Weight (NW / GW)	3.95 kg (8.7 lbs) / 6.5 kg (14.33 lbs)

FEATURES



180Hz High Refresh Rate

Experience smooth gaming with 180Hz refresh rate, that gives you the upperhand in fast moving games.



1500R Curved Gaming

Immerse in a captivating experience with a 1500R curvature rate.



Rapid VA


Provide ultra-fast 1ms GTG response time, make sure the intensity and purity of colors when gaming.



0.5ms (GtG, Min.) Response Time



200Hz High Refresh Rate Experience smooth gaming with a blazing fast 200Hz refresh rate, that gives you the upperhand in fast moving games.





Eliminate screen tearing and choppy frame rates with 0.5ms (GtG, Min.) Response Time.



HDR Ready

Enhance eye-catching details through adjustments in contrast



MONITOR MAG 276CFDE E20

Dimension with Stand (W x D x H)	610.5 x 249.8 x 451.6 mm (24 x 9.83 x 17.78 inch)
Dimension without Stand (W \mathbf{x} D \mathbf{x} H)	610.5 x 90.4 x 362.5 mm (24 x 3.56 x 14.27 inch)
Note	HDMI™: 1920 x 1080 (Up to 200Hz) DisplayPort: 1920 x 1080 (Up to 200Hz) Support: HDMI™ CEC; Non Support: KVM, PIP/PBP
Accessories	1x HDMI™ Cable (2.0), 1x Power Cord (C13), 1x Quick Guide

CONNECTIONS



- 1. OSD Button / 5-Way Navigator
- 2. AC-in
- 3. HDMI[™] 2.0b (FHD@180Hz)
- 4. DisplayPort 1.2a
- 5. HDMI[™] 2.0b (FHD@180Hz)
- 6. Headphone-out
- 7. Kensington Lock