



SPECIFICATIONS

Panel Size	31.5"
Panel Resolution	3840 x 2160 (UHD)
Refresh Rate	240Hz
Panel Type	QD-OLED
Brightness (nits)	SDR: 300 cd/m2 HDR: 1300 (Peak.)
Viewing Angle	178°(H) / 178°(V)
Aspect Ratio	16:9
Curvature	Flat
Contrast Ratio	1500000:1
Active Display Area (mm)	699.48(H) x 394.73(V)
Pixel Pitch (H x V)	0.1814 (H) x 0.1814 (V)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 138% (CIE1976 Standard)
Response time	0.03ms (GtG)
Video ports	2x HDMI™ 2.1 (UHD@240Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
USB ports	N/A
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48~240Hz
DCR	N/A
HDR Support	VESA DisplayHDR True Black 500
Signal Frequency	560.6~562.6 KHz(H) / 48~240 Hz(V)
Adjustment (Tilt)	-5° ~ 15°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Pivot)	-10° ~ 10°
Adjustment (Height)	0 ~ 110 mm
Carton Dimension (W X D X H)	975 x 185 x 515mm (38.3 x 7.2 x 20.2 inch)
Weight (NW / GW)	7.7 kg (16.9 lbs) / 12.38 kg (27.2 lbs)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.




VESA DisplayHDR True Black 500

It has passed the VESA DisplayHDR True Black 500 Certification, meaning it can provide a display with the most realistic colors.

Dimension with Stand (W x D x H)	719.1 x 241.9 x 483.9 mm (28.3 x 9.5 x 19 inch)
Dimension without Stand (W x D x H)	719.1 x 69.26 x 483.9 mm (28.3 x 2.7 x 19 inch)
Note	HDMI™: 3840 x 2160 (Up to 240Hz) DisplayPort: 3840 x 2160 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Accessories	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report

CONNECTIONS



1. Earphone out
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. Display Port 1.4a
4. USB Type-C (PD 15W)
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock