



SPECIFICATIONS


Panel Size	26.5"
Panel Resolution	2560 x 1440 (WQHD)
Refresh Rate	320Hz
Panel Type	QD-OLED
Brightness (nits)	SDR: 300 cd/m ² HDR: 1300 cd/m ² (Peak)
Viewing Angle	178° (H) / 178° (V)
Aspect Ratio	16:9
Curvature	Flat
Contrast Ratio	1500000:1 (Typ.)
Active Display Area (mm)	590.42(H) x 333.72(V)
Pixel Pitch (H x V)	0.2292(H) x 0.2292(V)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Adobe RGB / DCI-P3 / sRGB	98% / 99.7% / 143.73% (CIE1976 Standard)
Response time	0.03ms
Video ports	1x DisplayPort 1.4a (HBR3) 2x HDMI™ 2.1 (WQHD@320Hz) 1x Type-C (DP alt.) w/ 15W Power Delivery
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
VESA ClearMR Certified	VESA ClearMR 18000
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Premium Pro G-SYNC™ Compatible *Certifications may still be in progress. Please check the respective official websites for the latest compatibility list.
ACTIVATED RANGE	48~320Hz
DCR	N/A
HDR Support	VESA DisplayHDR True Black 500
Signal Frequency	507.52~524.28 KHz(H) / 48~320 Hz(V)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Pivot)	-90° ~ 90°

FEATURES



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.

VESA CERTIFIED



VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

Adjustment (Height)	0 ~ 110 mm
Carton Dimension (W x D x H)	870 x 165 x 505 mm (34.25 x 6.5 x 19.88 inch)
Weight (NW / GW)	8.06 kg (17.77 lbs) / 12.2 kg (26.9 lbs)
Dimension with Stand (W x D x H)	693 x 236.3 x 514.05 mm (27.28 x 9.3 x 20.24 inch)
Dimension without Stand (W x D x H)	609.3 x 71.7 x 361.8 mm (23.99 x 2.82 x 14.24 inch)
Note	HDMI™: 2560 x 1440 (Up to 320Hz) DisplayPort: 2560 x 1440 (Up to 320Hz) Type-C: 2560 x 1440 (Up to 320Hz) Support: HDMI™ CEC, PIP/PBP, Non Support: KVM
Accessories	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 1x Fiber Cloth, 1x Color Report

CONNECTIONS



- 1. AC-in
- 2. 5-way Navi Key
- 3. 2x HDMI™ 2.1
- 4. DisplayPort 1.4a (HBR3)
- 5. USB Type-C (15W PD)
- 6. Headphone-out
- 7. Kensington lock