MONITORS

MAG OLED 271QPX32







SPECIFICATIONS

Panel Size	26.5”
Active Display Area (mm)	590.42(H) x 333.72(V)
Curvature	Flat
Panel Type	QD-OLED
Panel Resolution	2560 x 1440 (WQHD)
Pixel Pitch (H x V)	0.2292(H) x 0.2292(V)
Aspect Ratio	16:9
Brightness (nits)	SDR: 300 cd/m² HDR: 1300 cd/m² (Peak)
Contrast Ratio	1500000:1 (Typ.)
DCR	N/A
Signal Frequency	507.52~524.28 KHz(H) / 48~320 Hz(V)
ACTIVATED RANGE	48~320Hz
Refresh Rate	320Hz
Response time	0.03ms
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Premium Pro G-SYNC™ Compatible *Certifications may still be in progress. Please check the respective official websites for the latest compatibility list.
HDR Support	VESA DisplayHDR True Black 500
Video ports	1x DisplayPort 1.4a (HBR3) 2x HDMI™ 2.1 (WQHD@320Hz) 1x Type-C (DP alt.) w/ 15W Power Delivery
Audio ports	1x Headphone-out
Viewing Angle	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	98% / 99.7% / 143.73% (CIE1976 Standard)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
VESA ClearMR Certified	VESA ClearMR 18000
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Pivot)	-90° ~ 90°
Adjustment (Height)	0 ~ 110 mm
Kensington Lock	Yes

FEATURES

165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games

Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming

OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.

0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.

VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

MAG OLED 271QPX32

Carton Dimension (W X D X H)	870 x 165 x 505 mm (34.25 x 6.5 x 19.88 inch)
Dimension with Stand (W x D x H)	609.3 x 236.3 x 414.1mm (24 x 9.3 x 16.3 inch)
Dimension without Stand (W x D x H)	609.3 x 72.3 x 361.9 mm (23.99 x 2.84 x 14.24 inch)
VESA Mounting	100 x 100 mm
Weight (NW / GW)	8.1 kg (17.86 lbs) / 12.2 kg (26.9 lbs)
Note	HDMI™: 2560 x 1440 (Up to 320Hz) DisplayPort: 2560 x 1440 (Up to 320Hz) Type-C: 2560 x 1440 (Up to 320Hz) Support: HDMI™ CEC, PIP/PBP, Non Support: KVM
Accessories	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 1x Fiber Cloth, 1x Color Report

CONNECTIONS



1. AC-in
2. 5-way Navi Key
3. 2x HDMI ™ 2.1
4. DisplayPort 1.4a (HBR3)
5. USB Type-C (15W PD)
6. Headphone-out
7. Kensington lock

Generated 2026-09-30, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.