



SPECIFICATIONS

Tamaño del panel	31.5"
Área de visualización activa (mm)	699.48 (H) x 394.73 (V)
Curvatura	Curve 1700R
Tipo de panel	QD-OLED
Resolución de la pantalla	3840x2160 (UHD)
Tamaño de píxel (H x V)	0.1814 (H) x 0.1814 (V)
Relación de aspecto	16:9
Brillo (Nits)	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Relación de contraste	1500000:1 (Typ.)
RANGO ACTIVADO	48 ~ 165Hz
Tasa de refresco	165Hz
Tiempo de respuesta	0.03ms (GTG)
TECNOLOGÍA DE TASA DE REFRESCO DINÁMICA	G-Sync Compatible
Admite HDR	DisplayHDR True Black 400
Puertos de video	1x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD
Puertos USB	N/A
Puertos de audio	1x Headphone-out
Ángulo de visión	178°(H) / 178°(V)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Tratamiento de la superficie	Anti-Reflection
Colores de pantalla	1.07B, 10 bits
Tipo de alimentación	100~240V, 50/60Hz
Entrada de alimentación	30~566KHz (H) / 48~240Hz (V)
Regulable (inclinación)	-5° ~ 15°
Regulable (Giro)	30° ~ 30°
Regulable (altura)	0 ~ 100mm
Kensington Lock	Yes
Tamaño de la caja (An X Pr X Al)	975 x 185 x 513mm (38.4 x 7.2 x 20.2 inch)
Diseño sin marcos	Yes
Soporte VESA	100 x 100 mm
Peso	8.0 kg (17.6 lbs) / 11.3 kg (24.9 lbs)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Dimension with Stand (W x D x H)	714 x 318 x 473 mm (28.1 x 12.5 x 18.6 inch)
Dimension without Stand (W x D x H)	714 x 123 x 423 mm (28.1 x 4.8 x 16.7 inch)
Accesorios	1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4) 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw
Garantía	3 years (including panel burn-in)
Observación	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMITM CEC, PIP/PBP; Non Support: KVM

CONNECTIONS



- 1. 2x HDMI™ 2.1 (UHD@165Hz)
- 2. 1x DisplayPort 1.4a
- 3. 1x Type-C (DP alt.) w/ 15W PD
- 4. Headphone-out
- 5. AC-in
- 6. Kensington Lock