



SPECIFICATIONS

Tamaño del panel	31.5"
Área de visualización activa (mm)	699.48(H) x 394.73(V)
Curvatura	Flat
Tipo de panel	QD-OLED
Resolución de la pantalla	3840 x 2160 (UHD)
Tamaño de píxel (H x V)	0.1814 (H) x 0.1814 (V)
Relación de aspecto	16:9
Brillo (Nits)	SDR: 300 cd/m2 HDR: 1000 (Peak.)
Relación de contraste	1500000:1
DCR	N/A
Rango tasa de refresco	48~240Hz
Tasa de refresco	240Hz
Tiempo de respuesta	0.03ms (GtG)
Admite HDR	VESA DisplayHDR True Black 500
Puertos de video	2x HDMI™ 2.1 (UHD@240Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Puertos USB	N/A
Puertos de audio	1x Headphone-out
Ángulo de visión	178°(H) / 178°(V)
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 138% (CIE1976 Standard)
Tratamiento de la superficie	Anti-Reflection
Colores de pantalla	1.07B, 10 bits
Tipo de alimentación	Internal Power Board
Entrada de alimentación	100~240V, 50/60Hz
Regulable (inclinación)	-5° ~ 15°
Regulable (Giro)	-30° ~ 30°
Regulable (Pivot)	-10° ~ 10°
Regulable (altura)	0 ~ 110 mm
Kensington Lock	Yes
Tecnología compatible	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
Tamaño de la caja (An X Pr X Al)	975 x 185 x 515mm (38.3 x 7.2 x 20.2 inch)
Soporte VESA	100 x 100 mm
Peso	7.7 kg (16.9 lbs) / 12.38 kg (27.2 lbs)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 500

It has passed the VESA DisplayHDR True Black 500 Certification, meaning it can provide a display with the most realistic colors.

Dimension with Stand (W x D x H)	719.1 x 241.9 x 483.9 mm (28.3 x 9.5 x 19 inch)
Dimension without Stand (W x D x H)	719.1 x 69.26 x 483.9 mm (28.3 x 2.7 x 19 inch)
Accesorios	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report
Observación	HDMI™: 3840 x 2160 (Up to 240Hz) DisplayPort: 3840 x 2160 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM

CONNECTIONS



1. Earphone out
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. Display Port 1.4a
4. USB Type-C (PD 15W)
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock