



SPECIFICATIONS

Tamaño del panel	34.18"
Área de visualización activa (mm)	800.06(H) x 337.06(V)
Curvatura	Curve 1800R
Tipo de panel	QD-OLED
Resolución de la pantalla	3440 x 1440 (UWQHD)
Tamaño de píxel (H x V)	0.2315(H) x 0.2315(V)
Relación de aspecto	21:9
Brillo (Nits)	SDR: 300 HDR: 1300
Relación de contraste	1500000:1 (Typ.)
DCR	N/A
Signal Frequency	461.2~464.8 KHz(H) / 48~280 Hz(V)
Rango tasa de refresco	48~280Hz
Tasa de refresco	280Hz
Tiempo de respuesta	0.03ms (GtG)
Admite HDR	VESA DisplayHDR True Black 500
Puertos de video	2x HDMI™ 2.1 (UWQHD@280Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Puertos de audio	1x Headphone-out
Ángulo de visión	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 136% (CIE1976 Standard)
Tratamiento de la superficie	Anti-Reflection
Colores de pantalla	1.07B, 10 bits
Tipo de alimentación	Internal Power Board
Entrada de alimentación	100~240V, 50/60Hz
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Regulable (Pivot)	-90° ~ 90°
Adjustment (Height)	0 ~ 110 mm
Kensington Lock	Yes
Tecnología compatible	Adaptive-Sync
VESA ClearMR Certified	VESA ClearMR 15000
Tamaño de la caja (An X Al X P)	1000 x 198 x 468 mm (39.37 x 7.80 x 18.43 inch)
Diseño sin marcos	Yes
Función PIP / PBP	Yes

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



280Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.




0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

Soporte VESA	100 x 100 mm
Peso	9.5 kg (20.94 lbs) / 14.4 kg (31.75 lbs)
Dimension with Stand (W x D x H)	811.7 x 229.9 x 430.4mm (31.96 x 9.05 x 16.94 inch)
Dimension without Stand (W x D x H)	811.7 x 131.3 x 361.2 mm (31.96 x 5.17 x 14.22 inch)
Accesorios	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report
Garantía	3 years (including panel burn-in)
Observación	HDMI™: 3440 x 1440 (Up to 280Hz) DisplayPort: 3440 x 1440 (Up to 280Hz) Type-C: 3440 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UWQHD@280Hz)
4. DisplayPort 1.4a
5. Type-C (DP alt.) w/ 15W PD
6. Headphone-out
7. Kensington Lock