



SPECIFICATIONS

Taille de la dalle	26.5"
Zone d'affichage active (mm)	590.42 (H) x 333.72 (V)
Courbure	Flat
Type de dalle	QD-OLED
Résolution	2560 x 1440 (WQHD)
Taille de pixel (H X V)	0.2292 (H) x 0.2292 (V)
Ratio	16:9
Luminosité	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Contraste	1500000:1 (Typ.)
Fréquence du signal	30~450.8KHz (H) / 48~280Hz (V)
Plage de fréquences de rafraîchissement	48~280Hz
Taux de rafraîchissement	280Hz
Temps de réponse	0.03ms (GtG)
Technologie de rafraîchissement dynamique	Adaptive-Sync
Support HDR	VESA DisplayHDR True Black 400
Angle de vision	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Affichage des couleurs	1.07B,10 bits
Traitement de la dalle	Anti-Reflection
Entrées vidéo	1x DisplayPort 1.4a (HBR3) 2x HDMI™ 2.1 (WQHD@280Hz) 1x Type-C (DP alt.) w/ 15W Power Delivery
Jacks audio	1x Headphone-out
Réglage de l'inclinaison	-5° ~ 20°
Réglage de la hauteur	0 ~ 110 mm
Réglage de l'angle de rotation	-30° ~ 30°
Rotation	-90° ~ 90°
Encoche Kensington	Yes
Type d'alimentation	Internal Power Board
Entrée alimentation	100~240V, 50/60Hz
Dimensions du carton (L x l x H)	820 x 169 x 513 mm (32.28 x 6.65 x 20.20 inch)

FEATURES

180Hz

180Hz High Refresh Rate

Experience smooth gaming with 180Hz refresh rate, that gives you the upperhand in fast moving games.



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming

280Hz

280Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.

0.03ms


Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Mode Console	Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz 1440p: 60Hz and 120Hz
	HDMI™ CEC: Supported VRR: PS5 and Xbox Supported
Design sans bordures	Yes
Fonctions PIP / PBP	Yes
Poids	6.8 kg (14.99 lbs) / 10.49 kg (23.13 lbs)
Fixation VESA	100 x 100 mm
Remarques	Display Port: 2560 x 1440 (Up to 280Hz) HDMI™: 2560 x 1440 (Up to 280Hz) Type-C (DP alt.): 2560 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Dimensions avec pied de support (L x H x P)	611.1 x 241.9 x 532.84 mm (24.06 x 9.52 x 20.98 inch)
Dimensions sans pied de support (L x H x P)	611.1 x 69.3 x 357.2 mm (24.06 x 2.73 x 14.06 inch)
Accessoires	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw
Garantie	3 years (including panel burn-in)

CONNECTIONS



- 1. Headphone-out
- 2. 2x HDMI™ 2.1 (WQHD@280Hz)
- 3. DisplayPort 1.4a (HBR3)
- 4. USB Type-C (15W PD)
- 5. 5-Way Navigator
- 6. AC-in
- 7. Kensington Lock