



## SPECIFICATIONS

Taille de la dalle	26.5"
Zone d'affichage active (mm)	589.97 (H) x 332.93 (V)
Courbure	Flat
Type de dalle	QD-OLED
Résolution	3840 x 2160 (UHD)
Taille de pixel (H X V)	0.153(H) x 0.153(V)
Ratio	16:9
Luminosité	SDR: 250 HDR: 1000
Contraste	1500000:1 (Typ.)
Contraste dynamique	N/A
Fréquence du signal	280.3~386.8 KHz(H) / 48~165 Hz(V)
Plage de fréquences de rafraîchissement	48~165Hz
Taux de rafraîchissement	165Hz
Temps de réponse	0.03ms (GtG)
Technologie de rafraîchissement dynamique	G-SYNC™ Compatible AMD FreeSync™ Premium Pro Technology
Support HDR	VESA DisplayHDR True Black 400
Angle de vision	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Affichage des couleurs	1.07B, 10 bits
Traitement de la dalle	Anti-Reflection
Entrées vidéo	2x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Jacks audio	1x Headphone-out
Réglage de l'inclinaison	-5° ~ 20°
Réglage de la hauteur	0 ~ 110 mm
Réglage de l'angle de rotation	-30° ~ 30°
Rotation	-90° ~ 90°
Encoche Kensington	Yes
Type d'alimentation	Internal Power Board
Entrée alimentation	100~240V, 50/60Hz
Design sans bordures	Yes
Fonctions PIP / PBP	Yes

## FEATURES



### QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



### 165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




### 0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



### OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



### Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



### VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

<b>Poids</b>	7.7 kg (16.9 lbs) / 10.9 kg (24 lbs)
<b>Fixation VESA</b>	100 x 100 mm
<b>Remarques</b>	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMITM CEC, PIP/PBP; Non Support: KVM
<b>Dimensions avec pied de support (L x H x P)</b>	611.1 x 241.9 x 532.8 mm (24 x 9.5 x 20.9 inch)
<b>Dimensions sans pied de support (L x H x P)</b>	611.1 x 69.3 x 357.2 mm (24 x 2.7 x 14 inch)
<b>Accessoires</b>	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Screw, 1x Fiber Cloth, 1x Color Report
<b>Garantie</b>	3 years (including panel burn-in)

## CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UHD@240Hz)
4. DisplayPort 2.1a (UHBR20)
5. USB Type-C (98W PD)
6. USB Type-B
7. 2x USB Type-A
8. Headphone-out
9. Kensington lock