



MONITORS G271C E2





## SPECIFICATIONS

Panel Size	27"
Active Display Area (mm)	596.736(H)x335.664(V)
Curvature	1000R
Panel Type	VA
Panel Resolution	1920x1080 (FHD)
Pixel Pitch (H x V)	0.3108(H)×0.3108(V)
Aspect Ratio	16:9
Brightness (nits)	300
Contrast Ratio	3000:1
DCR	10000000:1
Signal Frequency	103~186.8 KHz(H) / 48~170 Hz(V)
Refresh Rate	170Hz
Response time	1ms(MPRT)
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive sync
Video ports	2x HDMI <sup>™</sup> (Supports 1920x1080P@165Hz as specified in HDMI <sup>™</sup> 2.0b) 1x DP (Supports 1920x1080P@170Hz as specified in DisplayPort 1.2a by DP Overclocking)
Audio ports	1 x Earphone out
Viewing Angle	178°(H) / 178°(V)
Surface Treatment	Anti-glare
Display Colors	16.7M
Power Type	Power Cable
Power Input	100~240V, 50~60Hz
Adjustment (Tilt)	-5° ~ 20°
DCI-P3 / sRGB	85% / 115%
Kensington Lock	Yes
Power consumption	26W
Dimension (W x H x D)	606.5 x 245.6 x 482.2 mm / 23.88 x 9.67 x 18.98 inch
Carton Dimension (W X H X D)	780 x 448 x 188 mm / 30.71 x 17.64 x 7.4 inch
Console Mode	Yes
Frameless Design	Yes
VESA Mounting	75 x 75 mm
Weight (NW / GW)	5.6kg; 12.35 lbs / 7.8kg; 17.2 lbs


## **FEATURES**



# Curved Gaming™

View more of your game. MSI Curved Gaming<sup>™</sup> monitors are perfect for gamers to play their games.

### 1000R - The Perfect Curve



**IDDDR** Enjoy the most immersive gameplay with 1000R curvature



**170** Hz Experience smooth gaming with 170Hz refresh rate, that gives you the upperhand in fast moving games.

## Less Blue Light PRO

LESS BLUE LIGHT Use a hardware solution to reduce the light emission in the blueviolet region of the blue light spectrum (wavelength 415 to 455 nm).

#### **Frameless Design**

With the narrow bezel, you will not even notice the monitor at all in the heat of the moment.

### Wide Color Gamut

<u>M///</u> Wide Color Game colors and details will look more realistic and refined, to Gamut push game immersion to its limits.



MONITORS

G271C E2

Note

Display Port: 1920x1080 (Up to 170Hz) HDMI<sup>™</sup> 2.0: 1920x1080 (Up to 165Hz) \*sRGB and DCI-P3 follow CIE1976 standard

# CONNECTIONS



- 1. 1x HDMI<sup>™</sup> (2.0b)
- 1x HDMI<sup>™</sup> (2.0b)
  1x DisplayPort (1.2a)
- 4. 1x Earphone out
- 5. 1x Power Jack