



SPECIFICATIONS

Panel Size	26.5"
Kensington Lock	Yes
DYNAMIC REFRESH RATE TECHNOLOGY	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48~280Hz
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Carton Dimension (W X D X H)	820 x 169 x 513 mm (32.28 x 6.65 x 20.20 inch)
Rapporto d'aspetto	16:9
Risoluzione Pannello	2560 x 1440 (WQHD)
Pixel Pitch (H x V)	0.2292 (H) x 0.2292 (V)
Refresh Rate	280Hz
Tempo di risposta	0.03ms (GtG)
Angolo di Visualizzazione	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	611.1 x 241.9 x 532.84 mm (24.06 x 9.52 x 20.98 inch)
Curvatura	Flat
Dimension without Stand (W x D x H)	611.1 x 69.3 x 357.2 mm (24.06 x 2.73 x 14.06 inch)
Luminosità	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Contrasto	1500000:1 (Typ.)
Adjustment (Pivot)	-90° ~ 90°
Console Mode	Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz 1440p: 60Hz and 120Hz HDMI™ CEC: Supported VRR: PS5 and Xbox Supported
Frameless Design	Yes
Peso	6.8 kg (14.99 lbs) / 10.49 kg (23.13 lbs)
Panel Type	QD-OLED
Active Display Area (mm)	590.42 (H) x 333.72 (V)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Video ports	1x DisplayPort 1.4a (HBR3) 2x HDMI™ 2.1 (WQHD@280Hz) 1x Type-C (DP alt.) w/ 15W Power Delivery
Audio ports	1x Headphone-out

FEATURES

180Hz High Refresh Rate



Experience smooth gaming with 180Hz refresh rate, that gives you the upperhand in fast moving games.

QD-OLED Display



MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming

280Hz High Refresh Rate



Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.

Fastest 0.03 Response time




Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.

OLED Care 2.0



MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.

Graphene film with Custom Heatsink



Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA DisplayHDR True Black 400



It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
Signal Frequency	30~450.8KHz (H) / 48~280Hz (V)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Note	Display Port: 2560 x 1440 (Up to 280Hz) HDMI™: 2560 x 1440 (Up to 280Hz) Type-C (DP alt.): 2560 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
HDR Support	VESA DisplayHDR True Black 400
PIP / PBP Function	Yes
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. Headphone-out
2. 2x HDMI™ 2.1 (WQHD@280Hz)
3. DisplayPort 1.4a (HBR3)
4. USB Type-C (15W PD)
5. 5-Way Navigator
6. AC-in
7. Kensington Lock