



SPECIFICATIONS

Panel Size	26.5"
Kensington Lock	Yes
DYNAMIC REFRESH RATE TECHNOLOGY	NVIDIA G-SYNC Compatible
ACTIVATED RANGE	48~165Hz
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Rapporto d'aspetto	16:9
Risoluzione Pannello	3840 x 2160 (UHD)
Pixel Pitch (H x V)	0.153(H) x 0.153(V)
Refresh Rate	165Hz
Tempo di risposta	0.03ms (GtG)
Angolo di Visualizzazione	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	611.1 x 241.9 x 532.8 mm (24 x 9.5 x 20.9 inch)
Curvatura	Flat
Dimension without Stand (W x D x H)	611.1 x 69.3 x 357.2 mm (24 x 2.7 x 14 inch)
Luminosità	SDR: 250 HDR: 1000
Contrasto	1500000:1 (Typ.)
Adjustment (Pivot)	-90° ~ 90°
Frameless Design	Yes
Peso	7.7 kg (16.9 lbs) / 10.9 kg (24 lbs)
Panel Type	QD-OLED
DCR	N/A
Active Display Area (mm)	589.97 (H) x 332.93 (V)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Video ports	2x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Audio ports	1x Headphone-out
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
Signal Frequency	280.3~386.8 KHz(H) / 48~165 Hz(V)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

Adjustment (Height)	0 ~ 110 mm
Note	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMITM CEC, PIP/PBP; Non Support: KVM
HDR Support	VESA DisplayHDR True Black 400
PIP / PBP Function	Yes
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Screw, 1x Fiber Cloth, 1x Color Report
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UHD@240Hz)
4. DisplayPort 2.1a (UHBR20)
5. USB Type-C (98W PD)
6. USB Type-B
7. 2x USB Type-A
8. Headphone-out
9. Kensington lock