MONITOR

Optix MAG271CR





SPECIFICATIONS

DCI-P3 / sRGB	90% / Up ot 115%
Rapporto d'aspetto	16:9
Risoluzione Pannello	1920 x 1080
Pixel Pitch (H x V)	0.3114 (H) x 0.3114 (V)
Refresh Rate	144Hz
Tempo di risposta	1ms (MPRT)
Angolo di Visualizzazione	178°
Curvatura	1800R
Luminosità	300
Contrasto	3000:1
Dimensioni (W x H x D)	612.02 x 451.8 x 225.3mm
Frameless Design	Yes
Peso	5.6kg / 8kg
Panel Type	VA
DCR	100000000:1
Active Display Area (mm)	597.888(H) x 336.312(V)
Surface Treatment	Anti-glare
Display Colors	16.7M
Video ports	2 x HDMI™(1.4)
USB ports	2 x USB 2.0 1 x USB 2.0 Type B (PC to Monitor)
Audio ports	1 x Earphone out
VESA Mounting	100 x 100 mm
Power Type	Internal Adaptor
Power Input	100~240V, 50~60Hz
Signal Frequency	55.3 to 162KHz(H) 48 to 144Hz(V)
Adjustment (Tilt)	-5° ~ -20°
Adjustment (Height)	0 ~ 130 mm
Note	Display Port: 1920 x 1080 (Up to 144Hz) HDMI™: 1920 x 1080 (Up to 144Hz)

FEATURES

Mystic Light

Make your build look on fire or cold as ice. You are in control. Customize colors and effects with RGB LED.

CONNECTIONS

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.



1. 1x HDMI™
2. 1x HDMI™
3. 1x Display Port
4. 1x Headset
5. 2x USB 2.0 Type A
6. 1x USB 2.0 Type B
7. 1x Kensington Lock
8. Headset Hanger

Generated 2026-02-20, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.