



SPECIFICATIONS

DCI-P3 / sRGB	90% / 115%
Rapporto d'aspetto	16:9
Risoluzione Pannello	1920 x 1080 (FHD)
Pixel Pitch (H x V)	0.3114(H)X0.3114(V)
Refresh Rate	144Hz
Tempo di risposta	1ms(MPRT)
NTSC / sRGB	100% / 115%
Angolo di Visualizzazione	178°(H)/178°(V)
Curvatura	Yes
Luminosità	250 cd/m2
Contrasto	3000:1 (HDCR:100000000:1)
Consumi Energetici	65W, Standby < 0.5W, Off < 0.5W
I/O	1 x DP 1.2 - 1920 x 1080 (Up to 144Hz) 2 x HDMI™ 1.4 - 1920 x 1080 (Up to 144Hz)
Frameless Design	Yes
Dimensioni (W x H x D)	612 x 555.8 x 379.3mm / 24.09" x 21.88" x 14.93"
Peso	7.6kg / 16.76lbs (NW) 10.6kg / 23.37lbs (GW)
Note	Display Port: 1920 x 1080 (Up to 144Hz) HDMI™: 1920 x 1080 (Up to 144Hz) The color gamut follows the CIE 1976 testing standard.
Video ports	1x DP(1.2) 2x HDMI™(1.4)
Panel Type	VA
DCR	100000000:1
Active Display Area (mm)	597.888(H) x 336.312(V)
Surface Treatment	Anti-glare
Display Colors	16.7M
USB ports	2x USB 2.0 1x USB 2.0 Type B (PC to monitor)
Adjustment (Height)	0 ~ 120 mm
Audio ports	1x Headphone out 1x Mic in 1x Audio combo jack (PC to monitor)
VESA Mounting	100 mm x 100 mm
Power Type	External Adaptor 19V 3.42A
Power Input	100~240V, 50~60Hz
Signal Frequency	55.3 to 162KHz(H) 48 to 144Hz(V)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-40° ~ 40°

FEATURES



Mystic Light

Make your build look on fire or cold as ice. You are in control. Customize colors and effects with RGB LED.

CONNECTIONS



1. 1x HDMI™
2. 1x HDMI™
3. 1x Display Port
4. 1x USB 3.1 Gen 1 Type B
5. 1x Mic-in / Line-out Combo
6. 1x Kensington Lock
7. 1x Headset
8. 1x Mic
9. 2x USB 3.1 Gen 1 Type A