



SPECIFICATIONS

| | |
|--|--|
| DYNAMIC REFRESH RATE TECHNOLOGY | NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro |
| ACTIVATED RANGE | 48 ~ 165Hz |
| Adobe RGB / DCI-P3 / sRGB | 98% / 99% / 138% (CIE1976 Standard) |
| Carton Dimension (W x D x H) | 975 x 185 x 513mm (38.4 x 7.2 x 20.2 inch) |
| Panel Size | 31.5" |
| Aspect ratio | 16:9 |
| Panel Resolution | 3840x2160 (UHD) |
| Pixel Pitch (H x V) | 0.1814 (H) x 0.1814 (V) |
| Refresh Rate | 165Hz |
| Response time | 0.03ms (GTG) |
| Viewing angle | 178°(H) / 178°(V) |
| Dimension with Stand (W x D x H) | 714 x 318 x 473 mm (28.1 x 12.5 x 18.6 inch) |
| Curved | Curve 1700R |
| Dimension without Stand (W x D x H) | 714 x 123 x 423 mm (28.1 x 4.8 x 16.7 inch) |
| Brightness | SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL) |
| Contrast Ratio | 1500000:1 (Typ.) |
| Frameless Design | Yes |
| Weight | 8.0 kg (17.6 lbs) / 11.3 kg (24.9 lbs) |
| Panel Type | QD-OLED |
| Active Display Area (mm) | 699.48 (H) x 394.73 (V) |
| Surface Treatment | Anti-Reflection |
| Display Colors | 1.07B, 10 bits |
| Video ports | 2x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD |
| USB ports | N/A |
| Audio ports | 1x Headphone-out |
| Kensington Lock | Yes |
| VESA Mounting | 100 x 100 mm |
| Power Type | Internal Power Board |
| Power Input | 100~240V, 50/60Hz |
| Signal Frequency | 30~390KHz (H) / 48 ~ 165Hz(V) |

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GTG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

| | |
|----------------------------|--|
| Adjustment (Tilt) | -5° ~ 15° |
| Adjustment (Swivel) | 30° ~ 30° |
| Adjustment (Height) | 0 ~ 100mm |
| Note | HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMITM CEC, PIP/PBP; Non Support: KVM |
| HDR Support | DisplayHDR True Black 400 |
| Accessories | 1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4) 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw |
| Warranty | 3 years (including panel burn-in) |

CONNECTIONS



1. 2x HDMI™ 2.1 (UHD@165Hz)
2. 1x DisplayPort 1.4a
3. 1x Type-C (DP alt.) w/ 15W PD
4. Headphone-out
5. AC-in
6. Kensington Lock