



SPECIFICATIONS

Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Tecnología Dynamic Refresh Rate	Adaptive-Sync
ACTIVATED RANGE	48~240Hz
Adobe RGB / DCI-P3 / sRGB	98% / 99.1% / 138.4%
Dimension (W x D x H)	609 x 242 x 416mm 609 x 72 x 362mm (without stand)
Carton Dimension (W X D X H)	WW carton: 800 x 185 x 500mm Outer: 818 x 200 525 mm
Tamaño	26.5" (67.31cm)
Relación de aspecto	16:9
Resolución	2560x1440 (WQHD)
Pixel Pitch (H x V)	0.2292(H) x 0.2292(V)
Tasa de actualización	240Hz
Tiempo de respuesta	0.03ms (GtG)
Ángulo de visión	178°(H) / 178°(V)
Curvo	Flat
Brillo	SDR:250 nits HDR:450 nits (Typ.) (True Black 400 with 10% APL) 1000 nits (Typ.) (Peak 1000 with 3% APL)
Relación de contraste	1500000:1 (Typ.)
Adjustment (Pivot)	-90° ~ 90°
Frameless Design	Yes
Peso	8 kg / 10.3 kg
Tipo de panel	QD-OLED
DCR	N/A
Área de visión activa (mm)	590.42(H) x 333.72(V)
Tratamiento de superficie	Anti-Reflection
Colores	1.07B, 10 bits
Puertos de video	1 x DisplayPort (1.4a) 2 x HDMI™ 2.1 (WQHD@240Hz) 1 x USB 2.0 Type-C (DP alt.) w/ 15W PD
Puertos USB	N/A
Puertos de audio	1 x Headphone-out
Tipo de energía	Power Cable
Entrada de energía	100~240V, 50/60Hz
Frecuencia de señal	30~390 KHz(H) / 48~240 Hz(V)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.



240Hz Extremely High Refresh Rate

Experience smooth gaming with a blazing fast 240Hz refresh rate, that gives you the upper hand in fast moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Ajuste (Inclinación)	-5° ~ 20°
Ajuste (Rotación)	-30° ~ 30°
Ajuste (Altura)	0 ~ 110mm
Nota	Display Port: 2560 x 1440 (Up to 240Hz)
	HDMI 2.1: 2560 x 1440 (Up to 240Hz)
	Type C(DP alt.): 2560 x 1440 (Up to 240Hz) and 15W PD charging
	*Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard
Soporte HDR	DisplayHDR True Black 400
Función PIP / PBP	Yes
Warranty	3 years (including panel burn-in)

CONNECTIONS



- 1. AC-in
- 2. 5-way Joystick Navigator
- 3. 2 x HDMI™ 2.1
- 4. Display Port (1.4a)
- 5. USB Type-C (PD 15W)
- 6. Headphone out
- 7. Kensington lock