



SPECIFICATIONS

Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Tecnología Dynamic Refresh Rate	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium
ACTIVATED RANGE	48~240Hz
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Carton Dimension (W X D X H)	820 x 169 x 513mm (32.2 x 6.6 x 20.1 inch)
Tamaño	26.5"
Relación de aspecto	16:9
Resolución	2560 x 1440 (WQHD)
Pixel Pitch (H x V)	0.2292 (H) x 0.2292 (V)
Tasa de actualización	240Hz
Tiempo de respuesta	0.03ms (GtG)
Ángulo de visión	178°(H) / 178°(V)
Dimension with Stand (W x D x H)	611.6 x 533 x 241.9mm (24 x 20.9 x 9.5 inch)
Curvo	Flat
Dimension without Stand (W x D x H)	611.6 x 357.7 x 55.76mm (24 x 14 x 2.19 inch)
Brillo	SDR: 200 HDR: 400 (Typ.)
Relación de contraste	1500000:1 (Typ.)
Adjustment (Pivot)	-90° ~ 90°
	Supported Resolution & Refresh Rate: 1080p: 60Hz and 120Hz 1440p: 60Hz and 120Hz
Modo Consola	HDMI™ CEC: Supported / Non Supported VRR: Xbox only / PS5 and Xbox Supported
Peso	5.7 kg (12.5 lbs) / 9.4 kg (20.7 lbs)
Tipo de panel	QD-OLED
DCR	N/A
Área de visión activa (mm)	590.42 (H) x 333.72 (V)
Tratamiento de superficie	Anti-Reflection
Colores	1.07B, 10 bits

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.




Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

Puertos de video	2x HDMI™ 2.1 (FRL 10G) (WQHD@240Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Puertos USB	N/A
Puertos de audio	1x Headphone-out
Tipo de energía	Internal Power Board
Entrada de energía	100~240V, 50/60Hz
Frecuencia de señal	30~390 KHz(H) / 48~240 Hz(V)
Ajuste (Inclinación)	-5° ~ 20°
Ajuste (Rotación)	-30° ~ 30°
Ajuste (Altura)	0 ~ 110 mm
Nota	HDMI™: 2560 x 1440 (Up to 240Hz) DisplayPort: 2560 x 1440 (Up to 240Hz) Type-C: 2560 x 1440 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Soporte HDR	HDR Ready
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report

CONNECTIONS



1. Headphone out
2. 2 x HDMI™ 2.1 (WQHD@240Hz)
3. DisplayPort 1.4a (HBR3)
4. Type-C (DP alt.) w/ 15W PD
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock