MONITOR

MAG 274CQPDF X32







SPECIFICATIONS

Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Tecnología Dynamic Refresh Rate	AMD FreeSync™ Premium
ACTIVATED RANGE	WQHD: 48~320Hz HD: 48~400Hz
Adobe RGB / DCI-P3 / sRGB	90.3% / 95% / 132.5% (CIE1976 Standard)
Carton Dimension (W X D X H)	850 x 150 x 475 mm (33.46 x 5.91 x 18.70 inch)
Tamaño	27"
Relación de aspecto	16:9
Resolución	2560 x 1440 (WQHD)
Pixel Pitch (H x V)	0.2331 (H) x 0.2331 (V)
Tasa de actualización	WQHD : 320Hz HD : 400Hz
Tiempo de respuesta	0.5ms (GtG, Min.)
Ángulo de visión	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	613.5 x 278.3 x 403.7 mm (24.15 x 10.96 x 15.89 inch)
Curvo	Curve 1500R
Dimension without Stand (W x D x H)	613.5 x 78.3 x 363.6 mm (24.15 x 3.08 x 14.31 inch)
Weight Without Stand	3 kg (6.61 lbs)
Brillo	SDR: 350 cd/m² HDR: 450 cd/m²
Relación de contraste	5000:1
Adjustment (Pivot)	N/A
Peso	4.7 kg (10.36 lbs) / 7.7 kg (16.98 lbs)
Tipo de panel	Rapid VA
DCR	100000000:1
Área de visión activa (mm)	596.736 (H) x 335.664 (V)
Tratamiento de superficie	Anti-glare
Colores	1.07B, 10 bits (8 bits + FRC)
Puertos de video	1x DisplayPort 1.4a(HBR3) 2x HDMI™ 2.1 (WQHD@320Hz)
Puertos USB	N/A
Puertos de audio	1x Headphone-out
Tipo de energía	External Adaptor 19V 3.42A

FEATURES

Dual Mode

Easily switch between different resolutions and refresh rates, allowing user to adjust settings based on the game.

1500R Curved Gaming

Immerse in a captivating experience with a 1500R curvature rate.

Rapid VA

Deliver ultra-fast response, low latency, and fluid motion clarity for smooth, blur-free gaming with exceptional responsiveness.

0.5ms (GtG, Min.) Response Time

Eliminate screen tearing and choppy frame rates with 0.5ms (GtG, Min.) Response Time.

VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

Console Mode

Optimized for seamless compatibility with gaming consoles like PS5 and Xbox Series X|S.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

MONITOR

MAG 274CQPDF X32

Entrada de energía	100~240V, 50/60Hz
Frecuencia de señal	WQHD : 88.78~ 540.44 KHz(H) / 48~320 Hz(V) HD : 44.44~ 353.12 KHz(H) / 48~400 Hz(V)
Ajuste (Inclinación)	-5° ~ 20°
Ajuste (Rotación)	-30° ~ 30°
Ajuste (Altura)	0 ~ 130mm
Nota	HDMI™: QHD : 2560 x 1440 (Up to 320Hz) HD : 1280 x 720 (Up to 400Hz) DisplayPort: QHD : 2560 x 1440 (Up to 320Hz) HD : 1280 x 720 (Up to 400Hz) Support: HDMITM CEC, PIP/PBP; Non Support: KVM
Soporte HDR	VESA DisplayHDR 400
Accessories	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Power Adaptor, 1x Quick Guide, 4x Stand Screw
SPEAKER	N/A

CONNECTIONS



1. 5-Way Navi Key
2. DC-in
3. 2x HDMI™ 2.1 (WQHD@320Hz)
4. DisplayPort 1.4a
5. Headphone-out
6. Kensington Lock

Generated 2026-10-19, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.