



SPECIFICATIONS

Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
DYNAMIC REFRESH RATE TECHNOLOGY	G-Sync Compatible
ACTIVATED RANGE	48 ~ 165Hz
Adjustment (Swivel)	30° ~ 30°
Carton Dimension (W x D x H)	975 x 185 x 513mm (38.4 x 7.2 x 20.2 inch)
Panel Size	31.5"
Aspect ratio	16:9
Panel Resolution	3840x2160 (UHD)
Pixel Pitch (H x V)	0.1814 (H) x 0.1814 (V)
Refresh Rate	165Hz
Response time	0.03ms (GTG)
Viewing angle	178°(H) / 178°(V)
Dimension with Stand (W x D x H)	714 x 318 x 473 mm (28.1 x 12.5 x 18.6 inch)
Curved	Curve 1700R
Dimension without Stand (W x D x H)	714 x 123 x 423 mm (28.1 x 4.8 x 16.7 inch)
Brightness	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Contrast Ratio	1500000:1 (Typ.)
Frameless Design	Yes
Weight	8.0 kg (17.6 lbs) / 11.3 kg (24.9 lbs)
Panel Type	QD-OLED
Active Display Area (mm)	699.48 (H) x 394.73 (V)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Video ports	1x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD
USB ports	N/A
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	100~240V, 50/60Hz
Power Input	30~566KHz (H) / 48~240Hz (V)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Signal Frequency	30~390KHz (H) / 48 ~ 165Hz(V)
Adjustment (Tilt)	-5° ~ 15°
Adjustment (Height)	0 ~ 100mm
Note	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
HDR Support	DisplayHDR True Black 400
Accessories	1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4) 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. 2x HDMI™ 2.1 (UHD@165Hz)
2. 1x DisplayPort 1.4a
3. 1x Type-C (DP alt.) w/ 15W PD
4. Headphone-out
5. AC-in
6. Kensington Lock