



SPECIFICATIONS

ROZSTAW PIKSELI	0.2315(H) x 0.2315(V)
Porty Audio	1x Headphone-out
VESA ClearMR Certified	VESA ClearMR 15000
TECHNOLOGIA DYNAMIC REFRESH RATE	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
ZAKRES CZĘSTOTLIWOŚCI ODŚWIEŻANIA	48~280Hz
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 136% (CIE1976 Standard)
Rozmiar matrycy	34.18"
Proporcje obrazu	21:9
Rozdzielczość	3440 x 1440 (UWQHD)
Odświeżanie	280Hz
Czas reakcji	0.03ms (GtG)
Kąt widzenia	178° (H) / 178° (V)
Wymiary z podstawą (szer. x głęb. x wys.)	811.7 x 229.9 x 430.4mm (31.96 x 9.05 x 16.94 inch)
Zakrzywienie	Curve 1800R
Wymiary bez podstawy (szer. x głęb. x wys.)	811.7 x 131.3 x 361.2 mm (31.96 x 5.17 x 14.22 inch)
Jasność (Nity)	SDR: 300 HDR: 1300
Współczynnik kontrastu	1500000:1 (Typ.)
Carton Dimension (W X H X D)	1000 x 198 x 468 mm (39.37 x 7.80 x 18.43 inch)
Konstrukcja bezramkowa	Yes
Waga	9.5 kg (20.94 lbs) / 14.4 kg (31.75 lbs)
Typ panelu	QD-OLED
DCR	N/A
Aktywny obszar wyświetlania (mm)	800.06(H) x 337.06(V)
Powierzchnia matrycy	Anti-Reflection
Wyświetlane kolory	1.07B, 10 bits
Porty Wideo	2x HDMI™ 2.1 (UWQHD@280Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Kensington Lock	Yes
Montaż VESA	100 x 100 mm
Typ zasilania	Internal Power Board
Moc wejściowa	100~240V, 50/60Hz

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.

280Hz

280Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.

0.03ms


0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

Częstotliwość sygnału	461.2~464.8 KHz(H) / 48~280 Hz(V)
Regulacja (pochylenie)	-5° ~ 20°
Regulacja (obrót poziomy)	-30° ~ 30°
Regulacja (wysokość)	0 ~ 110 mm
Uwagi	HDMI™ : 3440 x 1440 (Up to 280Hz) DisplayPort: 3440 x 1440 (Up to 280Hz) Type-C: 3440 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Wsparcie HDR	VESA DisplayHDR True Black 500
Funkcje PIP / PBP	Yes
Akcesoria	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report
Gwarancja	3 years (including panel burn-in)

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UWQHD@280Hz)
4. DisplayPort 1.4a
5. Type-C (DP alt.) w/ 15W PD
6. Headphone-out
7. Kensington Lock