



SPECIFICATIONS

Refresh Rate	240Hz
DYNAMIC REFRESH RATE TECHNOLOGY	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48 ~ 240Hz
DCR	N/A
Panel Size	26.5"
Panel Resolution	2560 x 1440 (WQHD)
Response time	0.03ms (GTG)
Panel Type	QD-OLED
Brightness (nits)	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Viewing Angle	178°(H) / 178°(V)
Aspect Ratio	16:9
Curvature	Flat
Contrast Ratio	1500000:1 (Typ.)
Active Display Area (mm)	590.42 (H) x 333.72 (V)
Pixel Pitch (H x V)	0.2292 (H) x 0.2292 (V)
Carton Dimension (W x D x H)	800 x 185 x 500 mm (31.49 x 7.28 x 19.6 inch)
Surface Treatment	Anti-Reflection
Display Colors	1.07B, 10 bits
Video ports	2x HDMI™ 2.1 (WQHD@240Hz) 1x DisplayPort 1.4a (HBR3)
USB ports	N/A
Audio ports	1x Headphone-out
Kensington Lock	Yes
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
Dimension with Stand (W x D x H)	609 x 242 x 416 mm (23.9 x 9.52 x 16.37 inch)
Signal Frequency	30 ~ 390 KHz(H) / 48 ~ 240 Hz(V)
Dimension without Stand (W x D x H)	609 x 72 x 362 mm (23.9 x 2.8 x 14.25 inch)
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.




VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	100 x 100 mm
Weight (NW / GW)	8 kg (17.6 lbs) / 10.4 kg (22.92 lbs)
Note	HDMI™: 2560 x 1440 (Up to 240Hz) DisplayPort: 2560 x 1440 (Up to 240Hz) Support: HDMI™ CEC, Non Support: PIP/PBP, KVM
HDR Support	DisplayHDR True Black 400
Accessories	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2 x HDMI™ 2.1 (WQHD@240Hz)
4. Display Port 1.4a (HBR3)
5. Headphone out
6. Kensington lock