



SPECIFICATIONS

| | |
|---------------------------------|---|
| Refresh Rate | 240Hz |
| DYNAMIC REFRESH RATE TECHNOLOGY | Adaptive-Sync |
| ACTIVATED RANGE | 48 ~ 240Hz |
| Panel Size | 31.5" |
| Panel Resolution | 3840x2160 (UHD) |
| Response time | 0.03ms (GTG) |
| Panel Type | QD-OLED |
| Brightness (nits) | 250 |
| Adobe RGB / DCI-P3 / sRGB | 97.5%/99%/138.2% |
| Viewing Angle | 178°(H) / 178°(V) |
| Aspect Ratio | 16:9 |
| Curvature | Flat |
| Contrast Ratio | 1500000:1 |
| Active Display Area (mm) | 699.48(H) x 394.73(V) |
| Dimension (W x D x H) | 717 x 242 x 477 mm 717 x 72 x 419 mm (without stand) |
| Pixel Pitch (H x V) | 0.1814(H) x 0.1814(V) |
| Carton Dimension (W X D X H) | WW carton: 972 x 185 x 513 mm Outer: 1200 x 250 x 540 mm |
| Surface Treatment | Anti-Reflection |
| Display Colors | 1.07B, 10 bits |
| Video ports | 1x Display Port (1.4a) 2x HDMI™ (4K@240Hz) 1x Type-C (DP alt.) w/ PD 15W charging |
| Audio ports | 1x Headphone-out |
| Kensington Lock | Yes |
| Power Type | Power Cable |
| Power Input | 100~240V, 50/60Hz |
| Signal Frequency | 31~585 KHz(H) / 48~360 Hz(V) |
| Adjustment (Tilt) | -5° ~ 15° |
| Adjustment (Swivel) | 30° ~ 30° |
| Adjustment (Height) | 0 ~ 100mm |
| Adjustment (Pivot) | -10° ~ 10° |
| VESA Mounting | 100 x 100 mm |
| Weight (NW / GW) | 9.1 kg /11.4 kg |

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz Extremely High Refresh Rate

Experience smooth gaming with a blazing fast 240Hz refresh rate, that gives you the upper hand in fast moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

| | |
|---------------------------|--|
| Note | Display Port: 3840 x 2160 (Up to 240Hz) HDMI™: 3840 x 2160 (Up to 240Hz) Type C(DP alt.): 3840 x 2160 (Up to 240Hz) and 15W PD charging *sRGB and DCI-P3 follow CIE1976 standard |
| Frameless Design | Yes |
| HDR Support | DisplayHDR True Black 400 |
| PIP / PBP Function | N/A |
| Warranty | 3 years (including panel burn-in) |

CONNECTIONS



1. AC Power Jack
2. 5-way Joystick Navigator
3. 2 x HDMI™ (2.1)
4. Display Port (1.4a)
5. USB Type-C (PD 15W)
6. Earphone out
7. Kensington lock