



## SPECIFICATIONS

Response time	0.03ms (GtG)
<b>DYNAMIC REFRESH RATE TECHNOLOGY</b>	NVIDIA G-SYNC Compatible
<b>ACTIVATED RANGE</b>	48~165Hz
<b>Adobe RGB / DCI-P3 / sRGB</b>	98% / 99% / 138% (CIE1976 Standard)
<b>Panel Size</b>	26.5"
<b>Aspect ratio</b>	16:9
<b>Panel Resolution</b>	3840 x 2160 (UHD)
<b>Pixel Pitch (H x V)</b>	0.153(H) x 0.153(V)
<b>Refresh Rate</b>	165Hz
<b>Viewing angle</b>	178° (H) / 178° (V)
<b>Dimension with Stand (W x D x H)</b>	611.1 x 241.9 x 532.8 mm (24 x 9.5 x 20.9 inch)
<b>Curved</b>	Flat
<b>Dimension without Stand (W x D x H)</b>	611.1 x 69.3 x 357.2 mm (24 x 2.7 x 14 inch)
<b>Brightness</b>	SDR: 250 HDR: 1000
<b>Contrast Ration</b>	1500000:1 (Typ.)
<b>Adjustment (Pivot)</b>	-90° ~ 90°
<b>Frameless Design</b>	Yes
<b>Weight</b>	7.7 kg (16.9 lbs) / 10.9 kg (24 lbs)
<b>Panel Type</b>	QD-OLED
<b>DCR</b>	N/A
<b>Active Display Area (mm)</b>	589.97 (H) x 332.93 (V)
<b>Surface Treatment</b>	Anti-Reflection
<b>Display Colors</b>	1.07B, 10 bits
<b>Video ports</b>	2x HDMI™ 2.1 (UHD@165Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
<b>Audio ports</b>	1x Headphone-out
<b>Kensington Lock</b>	Yes
<b>VESA Mounting</b>	100 x 100 mm
<b>Power Type</b>	Internal Power Board
<b>Power Input</b>	100~240V, 50/60Hz
<b>Signal Frequency</b>	280.3~386.8 KHz(H) / 48~165 Hz(V)
<b>Adjustment (Tilt)</b>	-5° ~ 20°
<b>Adjustment (Swivel)</b>	-30° ~ 30°

## FEATURES



### QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



### 165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games




### 0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



### OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



### Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED



### VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

<b>Adjustment (Height)</b>	0 ~ 110 mm
<b>Note</b>	HDMI™: 3840 x 2160 (Up to 165Hz) DisplayPort: 3840 x 2160 (Up to 165Hz) Type-C: 3840 x 2160 (Up to 165Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
<b>HDR Support</b>	VESA DisplayHDR True Black 400
<b>PIP / PBP Function</b>	Yes
<b>Accessories</b>	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Screw, 1x Fiber Cloth, 1x Color Report
<b>Warranty</b>	3 years (including panel burn-in)

## CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UHD@240Hz)
4. DisplayPort 2.1a (UHBR20)
5. USB Type-C (98W PD)
6. USB Type-B
7. 2x USB Type-A
8. Headphone-out
9. Kensington lock