



SPECIFICATIONS

Display Colors	1.07B, 10 bits
Power Input	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Premium Pro
ACTIVATED RANGE	48~240Hz
HDR Support	VESA DisplayHDR True Black 500
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 138% (CIE1976 Standard)
Carton Dimension (W x D x H)	975 x 185 x 515mm (38.3 x 7.2 x 20.2 inch)
Panel Size	31.5"
Aspect ratio	16:9
Panel Resolution	3840 x 2160 (UHD)
Pixel Pitch (H x V)	0.1814 (H) x 0.1814 (V)
Refresh Rate	240Hz
Response time	0.03ms (GtG)
Viewing angle	178°(H) / 178°(V)
Dimension with Stand (W x D x H)	719.1 x 241.9 x 483.9 mm (28.3 x 9.5 x 19 inch)
Curved	Flat
Dimension without Stand (W x D x H)	719.1 x 69.26 x 483.9 mm (28.3 x 2.7 x 19 inch)
Brightness	SDR: 300 cd/m2 HDR: 1300 (Peak.)
Contrast Ration	1500000:1
Adjustment (Pivot)	-10° ~ 10°
Panel Type	QD-OLED
DCR	N/A
Active Display Area (mm)	699.48(H) x 394.73(V)
Surface Treatment	Anti-Reflection
Video ports	2x HDMI™ 2.1 (UHD@240Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
USB ports	N/A
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Signal Frequency	560.6~562.6 KHz(H) / 48~240 Hz(V)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

VESA CERTIFIED




VESA DisplayHDR True Black 500

It has passed the VESA DisplayHDR True Black 500 Certification, meaning it can provide a display with the most realistic colors.

Adjustment (Tilt)	-5° ~ 15°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Note	HDMI™: 3840 x 2160 (Up to 240Hz) DisplayPort: 3840 x 2160 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
Accessories	1x DisplayPort Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report

CONNECTIONS



1. Earphone out
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. Display Port 1.4a
4. USB Type-C (PD 15W)
5. 5-way Joystick Navigator
6. AC-in
7. Kensington lock