



## SPECIFICATIONS

Display Colors	1.07B, 10 bits
Power Input	100~240V, 50/60Hz
VESA ClearMR Certified	VESA ClearMR 15000
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
ACTIVATED RANGE	48~280Hz
HDR Support	VESA DisplayHDR True Black 500
Adobe RGB / DCI-P3 / sRGB	97% / 99% / 136% (CIE1976 Standard)
Panel Size	34.18"
Aspect ratio	21:9
Panel Resolution	3440 x 1440 (UWQHD)
Pixel Pitch (H x V)	0.2315(H) x 0.2315(V)
Refresh Rate	280Hz
Response time	0.03ms (GtG)
Viewing angle	178° (H) / 178° (V)
Dimension with Stand (W x D x H)	811.7 x 229.9 x 430.4mm (31.96 x 9.05 x 16.94 inch)
Curved	Curve 1800R
Dimension without Stand (W x D x H)	811.7 x 131.3 x 361.2 mm (31.96 x 5.17 x 14.22 inch)
Brightness	SDR: 300 HDR: 1300
Contrast Ration	1500000:1 (Typ.)
Adjustment (Pivot)	-90° ~ 90°
Carton Dimension (W X H X D)	1000 x 198 x 468 mm (39.37 x 7.80 x 18.43 inch)
Frameless Design	Yes
Panel Type	QD-OLED
DCR	N/A
Active Display Area (mm)	800.06(H) x 337.06(V)
Surface Treatment	Anti-Reflection
Video ports	2x HDMI™ 2.1 (UWQHD@280Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 15W PD
Audio ports	1x Headphone-out
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Internal Power Board
Signal Frequency	461.2~464.8 KHz(H) / 48~280 Hz(V)

## FEATURES



### QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



### 280Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.




### 0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



### OLED Care 3.0

MSI developing a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



### Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.



### VESA DisplayHDR 400

Enhance eye-catching details through adjustments in contrast and shadows.

<b>Adjustment (Tilt)</b>	-5° ~ 20°
<b>Adjustment (Swivel)</b>	-30° ~ 30°
<b>Adjustment (Height)</b>	0 ~ 110 mm
<b>Note</b>	HDMI™: 3440 x 1440 (Up to 280Hz) DisplayPort: 3440 x 1440 (Up to 280Hz) Type-C: 3440 x 1440 (Up to 280Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM
<b>PIP / PBP Function</b>	Yes
<b>Accessories</b>	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x Fiber Cloth, 1x Color Report
<b>Warranty</b>	3 years (including panel burn-in)

## CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UWQHD@280Hz)
4. DisplayPort 1.4a
5. Type-C (DP alt.) w/ 15W PD
6. Headphone-out
7. Kensington Lock