



SPECIFICATIONS

| | |
|---------------------------|--|
| 面板尺寸 | 26.5" |
| 顯示區域(MM) | 590.42 (H) x 333.72 (V) |
| 曲面螢幕 | Flat |
| 面板類型 | QD-OLED |
| 最佳解析度 | 2560 x 1440 (WQHD) |
| 像素 (H x V) | 0.2292 (H) x 0.2292 (V) |
| 螢幕比例 | 16:9 |
| 亮度 | SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL) |
| 靜態對比度 | 1500000:1 (Typ.) |
| 動態對比度(DCR) | N/A |
| 訊號頻率 | 96.24 ~ 265.98 KHz (H) / 48 ~ 240 Hz (V) |
| 更新頻率 | 240Hz |
| 反應時間 | 0.03ms (GtG) |
| 動態刷新率技術 | NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro |
| 支援HDR | DisplayHDR True Black 400 |
| 影像連接埠 | 2x HDMI™ 2.1 (WQHD@240Hz) 1x DisplayPort 1.4a (HBR3) |
| 音頻接孔 | 1x Headphone-out |
| 可視角度 | 178°(H) / 178°(V) |
| Adobe RGB / DCI-P3 / sRGB | 98% / 99% / 138% (CIE1976 Standard) |
| 表面處理 | Anti-Reflection |
| 色彩顯示 | 1.07B, 10 bits |
| 電源規格 | External Adaptor 24V 5A |
| 電源輸入 | 100~240V, 50/60Hz |
| 調整 (仰角) | -5° ~ 20° |
| 調整 (高度) | 0 ~ 130 mm |
| 調整 (左右旋轉) | -30° ~ 30° |
| 調整 (垂直旋轉) | -90° ~ 90° |
| 肯辛頓鎖孔 | Yes |
| 紙箱尺寸 (寬X深X高) | 780 x 140 x 475 mm (30.71 x 5.51 x 18.70 inch) |
| VESA安裝 | 100 x 100 mm |
| USB接孔 | N/A |
| 刷新率範圍 | 48 ~ 240Hz |

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.




Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.



VESA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

| | |
|--|--|
| Dimension with Stand (W x D x H) | 610.11 x 227.9 x 532.01 mm (24.02 x 8.97 x 20.95 inch) |
| Dimension without Stand (W x D x H) | 610.11 x 54.5 x 358.23 mm (24.02 x 2.15 x 14.10 inch) |
| 重量 (NW / GW) | 6.7 kg (14.77 lbs) / 9.65 kg (21.28 lbs) |
| 保固 | 3 years (including panel burn-in) |
| Accessories | 1x DisplayPort Cable (1.4a), 1x Power Cord (C5), 1x Power Adaptor, 1x Quick Guide, 2x Stand Screw, 4x VESA Wall Mount Screw |
| 備註 | HDMI™: 2560 x 1440 (Up to 240Hz) DisplayPort: 2560 x 1440 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP; Non Support: KVM |

CONNECTIONS



1. DC-in
2. Headphone-out
3. 5-way Joystick Navigator
4. 2x HDMI™ 2.1a (WQHD@240Hz)
5. DisplayPort 1.4a (HBR3)
6. Kensington Lock