



SPECIFICATIONS

Display Colors	1.07B (8 bits + FRC)
DYNAMIC REFRESH RATE TECHNOLOGY	Freesync premium
ACTIVATED RANGE	48 to 380Hz
HDR Support	VESA DisplayHDR 400
Adobe RGB / DCI-P3 / sRGB	85% / 83% / 106%
Dimension (W x D x H)	560 x 175 x 394 mm / 560 x 64 x 336 mm (without stand)
Carton Dimension (W X D X H)	WW carton: 761 x 207 x 410 mm / Outer: 776 x 222 x 435 mm
Panel Size	24.5" (62.2cm)
Aspect ratio	16:9
Panel Resolution	1920x1080 (FHD)
Pixel Pitch (H x V)	0.2829(H)x0.2802(V)
Refresh Rate	380Hz (Max. By DP Overclocking)
Response time	1ms GtG
Viewing angle	178° (H) / 178° (V)
Curved	Flat
Brightness	320 (Typ.) 400 (HDR Peak)
Contrast Ration	1000:1
Frameless Design	Yes
Console Mode	FHD@120Hz
Adjustment (Pivot)	N/A
Control	5-way Joystick Navigator
Weight	5.6 kg / 7.6 kg Without Stand: 3.3 kg
Panel Type	Rapid IPS
Surface Treatment	Anti-glare
DCR	100000000:1
Adjustment (Height)	0 ~ 130mm
Video ports	2x HDMI™ (Supports 1080P@240Hz as specified in HDMI™ 2.0b) 1x DisplayPort (Supports 1080P@380Hz as specified in DisplayPort 1.4a By DP overclocking)
PIP / PBP Function	N/A
Audio ports	1x Headphone out
Signal Frequency	150.9~417.6 KHz(H) / 48~380 Hz(V)
USB ports	N/A
Adjustment (Tilt)	-5° ~ 20°

FEATURES



Rapid IPS

Provides 1ms GTG fast response time, optimizes screen colors and brightness.



380Hz High Refresh Rate

Experience smooth gaming with a blazing-fast 380Hz refresh rate, that gives you the upper hand in fast-moving games by DP OverClocking.



Fast Response Time - 1ms GtG

Eliminate screen tearing and choppy frame rates with 1ms GTG response time.



Adjustable stand 2

Maximize your productivity and comfort with the adjustable stand.



VESA Certified DisplayHDR 400

Provide eye-catching detail through contrast and shadows adjustment.



G-Sync Compatible

Prevent screen tearing or stuttering, producing ultra-smooth lag-free gameplay.

Adjustment (Swivel)	N/A
Kensington Lock	Yes
VESA Mounting	75 x 75 mm
Note	Display Port: 1920 x 1080 (Up to 380Hz by DP Overclocking). HDMI™: 1920 x 1080 (Up to 240Hz) Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard
Power Type	Power Cable
Power Input	100~240V, 50/60Hz
Active Display Area (mm)	543.168(H)x302.616(V)

CONNECTIONS



1. 5-way Joystick Navigator
2. Kensington Lock
3. AC Power Jack
4. 2 x HDMI™ (2.0b)
5. 1 x Display Port (1.4a)
6. Earphone out