

Oculux NXG252R





SPECIFICATIONS

Panel Size	24.5" (62.2cm)
Active Display Area (mm)	543.744(H) x 302.616(V)
Panel Type	TN technology with LED backlight, low reflection
Panel Resolution	1920 x 1080 (FHD)
Pixel Pitch (H x V)	0.2832(H) x 0.2802(V)
Aspect Ratio	16:9
Brightness (nits)	400 nits
Contrast Ratio	1000:1
DCR	100000000:1
Signal Frequency	249.1 to 263KHz (H) 48 to 240Hz (V)
Refresh Rate	240Hz
Response time	0.5ms (GTG, Min.), 1ms (GTG, Avg.)
DYNAMIC REFRESH RATE TECHNOLOGY	G-Sync Compatible
Video ports	1x DP (1.2) 1x HDMI™ (1.4)
Audio ports	1x Earphone out
Viewing Angle	170° (H) / 160° (V)
Display Colors	16.7M
Power Type	External Adaptor 19V 3.42A
Power Input	100~240V, 50~60Hz
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height)	0 ~ 130mm
Dimension (W x H x D)	560.10 x 523.51 x 213.49 mm
Frameless Design	Yes
VESA Mounting	100 x 100 mm
USB ports	3x USB 3.1 Gen1 Type A 1x USB 3.1 Gen1 Type B (PC to Monitor)
Weight (NW / GW)	5.5kg / 8kg
Control	5-way OSD navigation joystick
Note	Display Port: 1920 x 1080 (Up to 240Hz) HDMI™: 1920 x 1080 (Up to 60Hz)
Power consumption	36W

FEATURES



240Hz Extremely High Refresh Rate

240_{Hz} Experience smooth gaming with a blazing fast 240Hz refresh rate, that gives you the upper hand in fast moving games.



NVIDIA G-SYNC

G-SYNC Take on any game without tearing, stuttering, flicker, or artifacts.



Extended USB hub design, easy to access USB device and charge to mobile device.



0.5ms Fast Response Time

0.5ms Eliminate screen tearing and choppy frame rates with 0.5ms response time.



Frameless Design

With the narrow bezel, you will not even notice the monitor at all in the heat of the moment.



Mystic Light

Make your build look on fire or cold as ice. You are in control. Customize colors and effects with RGB LED.



MONITOR Oculux NXG252R

CONNECTIONS



- 1. 1x HDMI™
- 2. 1x Display Port
- 3. 1x Earphone
- 4. 1x USB 3.1 Gen1 Type B
- 5. 3x USB 3.1 Gen1 Type A