

SPECIFICATIONS

| | |
|---|---|
| Format | Mid-Tower |
| Format de cartes mères supporté | Cartes mères standards : EATX (jusqu'à 305 x 278 mm), ATX, Micro-ATX, Mini-ITX Cartes mères à connecteurs inversés : ATX |
| Ports E/S | 1 x USB 20 Gb/s (Type-C) 2 x USB 5 Gb/s (Type-A) 1 x entrée audio / sortie audio 1 x bouton LED 1 x bouton de mise en marche |
| Baies de disques | 4 x 2,5" 1 x 3,5" 1 x combo 2,5"/3,5" |
| Slots d'extension du boîtier | 7 |
| Longueur maximum de la carte graphique | 400 mm |
| Longueur maximum du ventirad | 165 mm |
| Alimentation | ATX |
| Longueur maximum bloc d'alimentation | 200 mm |
| Taille de ventilateur supportée | Avant : 3 x 120 mm / 3 x 140 mm / 2 x 160 mm Arrière : 1 x 120 mm Haut : 3 x 120 mm / 3 x 140 mm Côté : 3 x 120 mm Emplacement de l'alimentation : 2 x 120 mm Bas : 1 x 120 mm |
| Ventilateur préinstallé | Avant : 2 x 160 mm Arrière : 1 x 120 mm |
| Type de ventilateurs préinstallés | Avant : 2 x ventilateurs ARGB (avec deux séries de pales) Arrière : 1 x ventilateur non-ARGB (avec deux séries de pales) |
| Longueur du radiateur | Avant : 120 / 140 / 240 / 280 / 360 mm Arrière : 120 mm Haut : 120 / 140 / 240 / 280 / 360 mm Côté : 120 / 240 / 360 mm Bas : N/A |
| Dimensions (DxWxH) | 485 x 235 x 518 mm |

FEATURES



Support Back Back-Connect ATX Motherboard

Compatible with ATX PROJECT ZERO motherboards, allowing easy installation and streamlined cable management by routing cables through the rear.



Airflow Optimized

Features a diamond diamond-cut ventilation front panel with two 16cm fans in the front and a 12cm fan at the rear, creating an optimized airflow channel.



Dual Layer Blades Fan

The dual-layer fan consists of outer and inner ring blades that rotate simultaneously, creating two airflow speeds for concentrated airflow and enhanced heat dissipation.



Versatile Cooling Support

Wide range of compatibility available for equipped up to 13 pieces of Fan, 3 pieces of 360mm Radiator, 1 piece of Pump Reservoir or one set of water cooling distro plate.



Fan Speed Control

Three fan speed levels provides customizable settings to suit various scenarios.



EZ PSU Cover


Quick snap-and-and-lock PSU cover enables easy assembly and streamlined cable management, optimizing the PC build process.



EZ Bracket

The adjustable EZ bracket supports fan sizes of 160mm x 2, 140mm x 3, and 120mm x 3, as well as a water cooling distro plate, allowing for flexible installation and optimized airflow.

CONNECTIONS



1. 1 x USB 20Gbps (Type-C)
2. 2 x USB 5Gbps (Type-A)
3. Mic In/ Audio Out
4. LED Button
5. Power Button