



SPECIFICATIONS

Format	Tour Micro- ATX
Format de cartes mères supporté	mATX (Support design back-connect) / ITX
Ports E/S	1 x USB 3.2 Gen1 Type-A 1 x USB 3.2 Gen2x2 Type-C 1 x entrée audio / sortie audio 1 x bouton de réinitialisation 1 x bouton de mise en marche
Baies de disques	1 x 2,5" 1 x combo 2,5"/3,5" (jusqu'à 2 x 2,5" ou 1 x 2,5" + 1 x 3,5")
Slots d'extension du boîtier	5
Longueur maximum de la carte graphique	390 mm * Support d'une installation horizontale seulement.
Longueur maximum du ventirad	175 mm
Alimentation	ATX
Longueur maximum bloc d'alimentation	200 mm
Taille de ventilateur supportée	Haut : 3 x 120 mm / 2 x 140 mm Avant : NA Arrière : 1 x 120 mm / 1 x 140 mm Côté : 3 x 120 mm Bas : 1 x 120 mm Cache alimentation : 2 x 120 mm
Ventilateur préinstallé	NA
Type de ventilateurs préinstallés	NA
Longueur du radiateur	Haut : 120 / 240 / 360 mm Avant : NA Arrière : 120 / 140 mm Côté : NA Bas : NA
Dimensions (L x l x H)	440 x 235 x 405 mm
Poids	8,8 kg
Poids brut	11,54 kg

FEATURES



Support Back-Connect Motherboard

Supporting back-connect motherboards enables easy installation without the worry of forgetting to connect cables, which might otherwise require disassembling graphics cards and coolers.



270-degree Panoramic Display

Drawing inspiration from the MAG logo, create a distinctive chassis design that embodies the unique MAG characteristics. The front interior of the chassis incorporates a space for displaying figurines, complemented by a 270-degree panoramic tempered glass, transforming it into a showcase-style chassis.



GPU Support Stand

Equipped with a level indicator to ensure effortless adjustment of the support height during installation, preventing sagging. Meanwhile, its magnetic base secures more stability within the chassis.



Dust Filter

The dust filters on the top and bottom are designed to give users the best experience in cleaning.

CONNECTIONS



1. 1x USB 3.2 Gen1 Type-A
2. 1x USB 3.2 Gen2x2 Type-C
3. Entrée audio / sortie audio
4. Bouton de réinitialisation
5. Bouton de mise en marche