

PRO MP165 E6

WORK SMART. PLAY HARD.





SPECIFICATIONS

响应时间	刷新率	60Hz
RATIO)	响应时间	4ms (GtG)
比例	•	100000000:1
Ba	亮度 (尼特)	250
RF	比例	16:9
显示区域(mm) 点距 (H X V) POWER INPUT 100~240V, 50/60Hz 扬声器 三脚架接口 1/4" Standard Tripod Socket VESA MOUNTING 75 x 75mm 6仲调节 0 ~ 90° DIMENSION (W X D X H) 1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) CARTON DIMENSION (W X D X H) R Dimension (W X D X H) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) R Dimension (W X D X H) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Type-A to Type-C to Type-C to Type-C cable, 1x Type-A to Type-C to Type-C to Type-C cable, 1x Type-A to Type-C to Type-C to Type-C cable, 1x Type-A to Type-C to Type-C to Type-C cable, 1x Type-A to Type-C to Type-C to Type-C cable, 1x Type-A to Type-C t	曲率	Flat
点距 (H X V) POWER INPUT 100~240V, 50/60Hz 扬声器 2x 1W 三脚架接口 75 x 75mm 6仲调节 0~90° DIMENSION (W X D X H) 1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) CARTON DIMENSION (W X D X H) CARTON DIMENSION (W X D X H) R寸 15.6" 分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) External USB Power (Type C interface)	sRGB	49.51% (CIE 1976)
POWER INPUT	显示区域(mm)	344.16(H) x 193.59 (V)
Sp	点距 (H X V)	0.17925(H) x 0.17925(V)
三脚架接口	POWER INPUT	100~240V, 50/60Hz
VESA MOUNTING 75 x 75mm 俯仰调节 0 ~ 90° DIMENSION (W X D X H) 356.5 x 13.85 x 210.35 mm (14.04 x 0.55 x 8.28 inch) 视频接口 1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 配件 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) 416 x 53 x 290 mm (16.38 x 2.09 x 11.42 inch) 尺寸 15.6" 分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	扬声器	2x 1W
俯仰调节 0~90° DIMENSION (W X D X H) 356.5 x 13.85 x 210.35 mm (14.04 x 0.55 x 8.28 inch) 1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) 416 x 53 x 290 mm (16.38 x 2.09 x 11.42 inch) 尺寸 15.6" 分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) External USB Power (Type C interface)	三脚架接口	1/4" Standard Tripod Socket
DIMENSION (W X D X H) 356.5 x 13.85 x 210.35 mm (14.04 x 0.55 x 8.28 inch) 1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) CARTON DIMENSION (W X D X H) X H) 15.6" 15.6" 1920 x 1080 (FHD) □板类型 □板类型 □ 1920 x 1080 (FHD) □板类型 □ 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) External USB Power (Type C interface)	VESA MOUNTING	75 x 75mm
(14.04 x 0.55 x 8.28 inch)	俯仰调节	0 ~ 90°
2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input) 1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide CARTON DIMENSION (W X D X H) CARTON DIMENSION (W X D X H) P寸 15.6" 分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	DIMENSION (W X D X H)	
配件1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick GuideCARTON DIMENSION (W X D X H)416 x 53 x 290 mm (16.38 x 2.09 x 11.42 inch)尺寸15.6"分辨率1920 x 1080 (FHD)耐板类型IPS对比度1000:1表面处理Anti-glare发色数16.7M, 8 bits (6 bits + FRC)电源类型External USB Power (Type C interface)	视频接口	2x Type-C (DP 1.2a signal with Alt mode &
X H) (16.38 x 2.09 x 11.42 inch) 尺寸 15.6" 分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	配件	1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable,
分辨率 1920 x 1080 (FHD) 面板类型 IPS 对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	•	
面板类型IPS对比度1000:1表面处理Anti-glare发色数16.7M, 8 bits (6 bits + FRC)电源类型External USB Power (Type C interface)	尺寸	15.6"
对比度 1000:1 表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	分辨率	1920 x 1080 (FHD)
表面处理 Anti-glare 发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	面板类型	IPS
发色数 16.7M, 8 bits (6 bits + FRC) 电源类型 External USB Power (Type C interface)	对比度	1000:1
电源类型 External USB Power (Type C interface)	表面处理	Anti-glare
	发色数	16.7M, 8 bits (6 bits + FRC)
角重 / 毛重 0.78 kg (1.72 lhs) / 1.6 kg (3.53 lhs)	电源类型	External USB Power (Type C interface)
<u>17年 / 七重 0.70 kg (1.72 lb3) / 1.0 kg (5.55 lb3)</u>	净重 / 毛重	0.78 kg (1.72 lbs) / 1.6 kg (3.53 lbs)
A注 HDMI™: 1920 x 1080 (Up to 60Hz) Type-C: 1920 x 1080 (Up to 60Hz)	备注	· · · · · · · · · · · · · · · · · · ·

FEATURES



Ultra Slim & Portable Design

Bring it anywhere you want without any strain or pressure.



1/4-inch Tripod Mount Support



The 1/4-inch tripod socket enhances flexibility for convenient placement by your side.



L-Shaped Cable

L-shaped cables prevent cable bending, ensuring convenience and uninterrupted use.



Full HD IPS Panel

Make sure the intensity and purity of colors when gaming.



Type C Display

Allows you to connect the latest devices more conveniently and with less trouble.



Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.



Eye-Q Check

Help have self-check eyes & remind to take a rest while using the monitor for a long time.



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.



Post-Consumer Recycled Material (PCR)

Using post-consumer recycled material in monitor bodies to minimize environmental impact and promote sustainability.



PRO MP165 E6

WORK SMART. PLAY HARD.

CONNECTIONS



- 1. 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
- 2. 1x HDMI™ 2.0b (FHD@60Hz)
- 3. 1x Headphone-out
- 4. OSD Button
- 5. Power Button
- 6. 1/4" Standard Tripod Socket
- 7. VESA Mount Socket