



SPECIFICATIONS

PANEL SIZE	15.6"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	60Hz
RESPONSE TIME	4ms (GtG)
PANEL TYPE	IPS
BRIGHTNESS (NITS)	250
ASPECT RATIO	16:9
CONTRAST RATIO	1000:1
SRGB	45.1 % (CIE 1976)
ACTIVE DISPLAY AREA (MM)	344.16(H) x 193.59 (V)
CURVATURE	Flat
PIXEL PITCH (H X V)	0.17925(H) x 0.17925(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M, 8 bits (6 bits + FRC)
SPEAKER	1W x2
VIDEO PORTS	1x mini-HDMI™ 1.4b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
TRIPOD SOCKET	1/4" Standard Tripod Socket
POWER TYPE	USB Cable
ADJUSTMENT (TILT)	0° ~ 180°
Accessory	1x L-shaped mini-HDMI cable (1.5M), 1x L-shaped Type-C cable (1M), 1x Type-A to Type-C cable (1.5M), 1x Protection Pouch, 1x Quick Guide
SIGNAL FREQUENCY	67.2~67.2 KHz(H) / 60~60 Hz(V)
AUDIO PORTS	1x Headphone-out
WEIGHT (NW / GW)	0.89 kg (1.96 lbs) / 1.67 kg (3.68 lbs)
Note	HDMI™: 1920 x 1080 (Up to 60Hz) Type-C: 1920 x 1080 (Up to 60Hz)
DCR (DYNAMIC CONTRAST RATIO)	100000000:1
Adjustment (Pivot)	0 ~ 360°
POWER INPUT	100~240V, 50/60Hz
VESA MOUNTING	75 x 75mm
Dimension with Stand (W x D x H)	356.35 x 22.20 x 274.32 mm (14.03 x 0.87 x 10.8 inch)
Dimension without Stand (W x D x H)	356.35 x 13.5 x 210.47 mm (14.03 x 0.53 x 8.29 inch)

FEATURES




Ultra Slim & Portable Design

Bring it anywhere you want without any strain or pressure.



1/4-inch Tripod Mount Support

The 1/4-inch tripod socket enhances flexibility for convenient placement by your side.



L-Shaped Cable

L-shaped cables prevent cable bending, ensuring convenience and uninterrupted use.



Type C Display

Allows you to connect the latest devices more conveniently and with less trouble.



Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.

CARTON DIMENSION (W X D X H) 416 x 53 x 290 mm
(16.38 x 2.09 x 11.42 inch)

CONNECTIONS



1. Headphone-out
2. OSD Button
3. Power Button
4. 1x mini-HDMI™ 1.4b (FHD@60Hz)
5. 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)