



SPECIFICATIONS

PANEL SIZE	15.6"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	60Hz
RESPONSE TIME	4ms (GtG)
PANEL TYPE	IPS
BRIGHTNESS (NITS)	250
ASPECT RATIO	16:9
CONTRAST RATIO	1000:1
SRGB	49.51% (CIE 1976)
ACTIVE DISPLAY AREA (MM)	344.16(H) x 193.59 (V)
CURVATURE	Flat
PIXEL PITCH (H X V)	0.17925(H) x 0.17925(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M, 8 bits (6 bits + FRC)
SPEAKER	2x 1W
VIDEO PORTS	1x HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
TRIPOD SOCKET	1/4" Standard Tripod Socket
POWER TYPE	External USB Power (Type C interface)
ADJUSTMENT (TILT)	0 ~ 90°
Accessory	1x L-shaped right angle HDMI™ cable, 1x L-shaped right angle Type-C to Type-C cable, 1x Type-A to Type-C cable, 1x Protection Pouch, 1x Quick Guide
WEIGHT (NW / GW)	0.78 kg (1.72 lbs) / 1.6 kg (3.53 lbs)
Note	HDMI™: 1920 x 1080 (Up to 60Hz) Type-C: 1920 x 1080 (Up to 60Hz)
DCR (DYNAMIC CONTRAST RATIO)	100000000:1
POWER INPUT	100~240V, 50/60Hz
VESA MOUNTING	75 x 75mm
DIMENSION (W X D X H)	356.5 x 13.85 x 210.35 mm (14.04 x 0.55 x 8.28 inch)
CARTON DIMENSION (W X D X H)	416 x 53 x 290 mm (16.38 x 2.09 x 11.42 inch)

FEATURES



5G Network Solution

Featuring premium 5G LAN to deliver better network experience.



5G Network Solution

Featuring premium 5G LAN to deliver better network experience.



5G Network Solution

Featuring premium 5G LAN to deliver better network experience.

CONNECTIONS



1. 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
2. 1x HDMI™ 2.0b (FHD@60Hz)
3. 1x Headphone-out
4. OSD Button
5. Power Button
6. 1/4" Standard Tripod Socket
7. VESA Mount Socket