



- Cabo 12V-2x6 bicolor
- Pronta para ATX 3.1
- Pronta para PCIe 5.1 (300W)
- 80 PLUS Bronze
- Fan de 120mm
- Projeto de alimentação DC to DC
- Design com PFC ativo
- Proteções em nível industrial com OVP, OCP, SCP, OPP, UVP

SPECIFICATIONS

| | |
|------------------------------|---|
| Model Name | TORX FAN 12CM |
| WEIGHT (CARD) | 169g |
| Dimensions | 120mm x 120mm x 25.6mm |
| Modular | No |
| Bearing Type | Hydro-Dynamic Bearing |
| Fan Bearing | Hydraulic Bearing |
| Rated Speed | 500 - 1800 ±15% RPM |
| Potência Watt | 650W |
| Power Excursion | 200% |
| Air Flow | 19.79 - 71.27 CFM |
| Voltagem de Entrada | 100-240V~ |
| Static Air Pressure | 0.16 - 2.09 mm-H2O |
| Frequência de entrada | 50-60Hz |
| Connector | 4-Pin PWM/DC |
| Eficiência | 80 PLUS Bronze (up to 85%) |
| EPS (8 pin) | 1 |
| Life Expectancy | MTTF 150,000 Hours (25°C) |
| ATX (24 pin) | 1 |
| PCI-E 5.1 (16 pin) | 1 (300W) |
| Tamanho do ventilador | 120 mm |
| EPS (8 pin) | 1 |
| Dimensões | 140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches |
| PCI-E (6+2 pin) | 2 |
| Tipo de PFC | Active PFC |
| SATA (15 pin) | 3 |
| Proteção | OVP, OCP, SCP, OPP, UVP |
| MOLEX (4 pin) | 2 |

MAG A650BN PCIE5 II

AC INPUT

100-240V~, 10A, 50-60Hz

| MAG A650BN PCIE5 II | | | | |
|---------------------|------|-------|------|-------|
| DC OUTPUT | +5V | +3.3V | +12V | +5Vsb |
| | 20A | 20A | 54A | 3A |
| TOTAL POWER | 120W | | 648W | 15W |
| | 650W | | | |

| CONNECTOR | | | | | |
|-----------|-----|-----------|-------|------|------------|
| ATX | EPS | PCI-E 5.1 | PCI-E | SATA | PERIPHERAL |
| 1 | 2 | 1 | 2 | 3 | 2 |