



- ATX 3.1 ready, native dual-color PCIe CEM 5.1 connector
- Supports NVIDIA® GeForce RTX™ 40 series graphics cards
- Fully modular design, flat cables
- 80 PLUS Gold certified for high efficiency
- Active PFC design
- Protection with OVP / OCP / OPP / OTP / SCP / UVP
- 135 mm fluid dynamic bearing fan
- LLC full bridge topology with DC-to-DC module design

SPECIFICATIONS

电源瓦数	1250W
效能	80 PLUS Gold (up to 90%)
模组	Yes (fully modular)
风扇尺寸	135 mm
风扇轴承	Fluid Dynamic Bearing
保护	OCP / OVP / OPP / OTP / SCP / UVP
PFC类型	Active PFC
输入频率	50-60Hz
输入电压	100-240V~
尺寸	150 x 150 x 86 mm
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E (6+2 pin)	4
SATA (15 pin)	12
MOLEX (4 pin)	4
FDD (4 pin)	1
峰值功率	2500W (*up to 200% of the PSU's rated power for 100µs)
PCI-E 5.1 (16 pin)	1 (600W)

MAG A1250GL PCIE5					
AC INPUT	100-240V~, 15A , 50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	22A	22A	104.1A	0.3A	3A
TOTAL POWER	120W	1249W	3.6W	15W	
	1250W				



POWER-SUPPLY
MAG A1250GL PCIE5

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	Molex	FDD
1	2	1	4	12	4	1