



- Doppeltes 12-V-2x6-Kabel
- ATX 3.1-kompatibel
- PCIe 5.1-kompatibel (300 W)
- 80 PLUS Bronze
- 120-mm-Lüfter
- DC-zu-DC-Stromversorgung
- Aktives PFC-Design
- Schutz auf Industrie-Niveau mit OVP, OCP, SCP, OPP, UVP

SPECIFICATIONS

Efficiency Rating	80 PLUS Bronze (up to 85%)
Modular	No
Fan Bearing	Hydraulic Bearing
Power Watt	650W
Power Excursion	200%
Input Voltage	100-240V~
Input Frequency	50-60Hz
ATX (24 pin)	1
EPS (4+4 PIN)	2
PCI-E 5.1 (16 pin)	1 (300W)
Fan Size	120 mm
Dimensions (DxWxH)	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	2
PFC Type	Active PFC
SATA (15 pin)	3
Protection	OVP, OCP, SCP, OPP, UVP
MOLEX (4 pin)	2

MAG A650BN PCIE5 III

AC INPUT	100-240V~, 10-5A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	15A	15A	54A	2.5A
TOTAL POWER	100W		648W	12.5W
	650W			

CONNECTOR



POWER - SUPPLY
MAG A650BN PCIE5 III
YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	2	3	2