



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1-kompatibel
- 105 °C Hauptelektrolytkondensator
- 80 PLUS Platinum-Zertifizierung
- Geprägte, zertifizierte Kabel
- Industrieller Schutz mit OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO

SPECIFICATIONS

WEIGHT (CARD)	169g
Efficiency Rating	80 PLUS Platinum (up to 92%)
Dimensions	120mm x 120mm x 25.6mm
Modular	Fully Modular
Fan Bearing	Hydraulic Bearing
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Power Watt	1000W
Power Excursion	200%
Input Voltage	100-240V~
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Input Frequency	50-60Hz
Connector	4-Pin PWM/DC
ATX (24 pin)	1
Life Expectancy	MTTF 150,000 Hours (25°C)
EPS (4+4 PIN)	2
PCI-E 5.1 (16 pin)	1 (600W)
Fan Size	120 mm
Dimensions (DxWxH)	150 x 150 x 86 mm / 5.9 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	3
PFC Type	Active PFC
SATA (15 pin)	6
Protection	OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO
MOLEX (4 pin)	2

PRO A1000PL PCIE5

AC INPUT	100-240V~, 13-6.5A, 50-60Hz				
DC OUTPUT	+5V	+3V	+12V	-12V	+5Vsb
	20A	20A	83.3A	0.3A	2.5A



POWER - SUPPLY

PRO A1000PL PCIE5

YOUR POWER, RIGHT AWAY

PRO A1000PL PCIE5

TOTAL POWER	100W	999.6W	3.6W	12.5W
1000W				

CONNECTOR

ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	6	2