



- Zweifarbiges 12-V-2x6-Kabel
- ATX 3.1-kompatibel
- PCIe 5.1-kompatibel (600 W)
- 105 °C Hauptelektrolytkondensator
- 80 PLUS Platinum-Zertifizierung
- Geprägte, zertifizierte Kabel
- Industrieller Schutz mit OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO

**SPECIFICATIONS**

<b>WEIGHT (CARD)</b>	169g
<b>Efficiency Rating</b>	80 PLUS Platinum (up to 92%)
<b>Dimensions</b>	120mm x 120mm x 25.6mm
<b>Modular</b>	Fully Modular
<b>Fan Bearing</b>	Hydraulic Bearing
<b>Bearing Type</b>	Hydro-Dynamic Bearing
<b>Rated Speed</b>	500 - 1800 ±15% RPM
<b>Power Watt</b>	850W
<b>Power Excursion</b>	200%
<b>Input Voltage</b>	100-240V~
<b>Air Flow</b>	19.79 - 71.27 CFM
<b>Static Air Pressure</b>	0.16 - 2.09 mm-H2O
<b>Input Frequency</b>	50-60Hz
<b>Connector</b>	4-Pin PWM/DC
<b>ATX (24 pin)</b>	1
<b>Life Expectancy</b>	MTTF 150,000 Hours (25°C)
<b>EPS (4+4 PIN)</b>	2
<b>PCI-E 5.1 (16 pin)</b>	1 (600W)
<b>Fan Size</b>	120 mm
<b>Dimensions (DxWxH)</b>	150 x 150 x 86 mm / 5.9 x 5.9 x 3.38 inches
<b>PCI-E (6+2 pin)</b>	3
<b>PFC Type</b>	Active PFC
<b>SATA (15 pin)</b>	6
<b>Protection</b>	OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO
<b>MOLEX (4 pin)</b>	2

**PRO A850PL PCIE5**

<b>AC INPUT</b>	100-240V~, 12-6.3A, 50-60Hz				
<b>DC OUTPUT</b>	<b>+5V</b>	<b>+3.3V</b>	<b>+12V</b>	<b>-12V</b>	<b>+5Vsb</b>
	20A	20A	70.8A	0.3A	2.5A



POWER-SUPPLY

## PRO A850PL PCIE5

YOUR POWER, RIGHT AWAY

### PRO A850PL PCIE5

TOTAL POWER	100W	849.6W	3.6W	12.5W
850W				

### CONNECTOR

ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	6	2