



- Premium protection, GPU Safeguard and Fan Safeguard
- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- Native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Platinum certified
- Optimized the sound level
- Main 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

SPECIFICATIONS

Efficiency Rating	80 PLUS Platinum (up to 92%)
Modular	Yes (full modular)
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86mm / 5.9 x 5.9 x 3.4 inches
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	1000W
Input Frequency Range	50-60Hz
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
EPS (8 pin)	1
EPS (4+4 pin)	1
PCI-E 5.1 (16 pin)	1 (600W)
PCI-E (6+2 pin)	4
SATA (15 pin)	6
PERIPHERAL (4 pin)	3

MAG A1000PLS PCIE5

AC INPUT	100-240V~, 15.0A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	20A	20A	83.3A	3A
TOTAL POWER	100W	999.6W	15W	
	1000W			

CONNECTOR



POWER - SUPPLY

MAG A1000PLS PCIE5

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	4	6	3